Remingion.

REMINGTON ARMS COMFANY, INC.

SPORTING ARMS-AMMUNITION-TARGETS-TRAPS

January 4, 1982

Gell's Sporting Goods #6 17242 Greydale Detroit, Michigan 48219

Gentlemen:

, 1 - 1

Examination has been completed on the Model 700 BDL L.H. 30-06 Springfield caliber rifle, serial number A6827002, which you returned to us when it allegedly fired as the safety was moved to the "fire" position.

The returned firearm, which was produced in October of 1979, has been examined by our firearms experts who report that it contained our highpressure proof test, gallery test, and final inspection stampings, indicating that it had successfully passed all our necessary tests prior to shipment.

The general condition of the gun appeared to be new; however, it was noted that there were some slight mars on the stock. In going over the individual parts, we found the headspace, recoil shoulders, and chamber all to be normal.

Examination of the rifle and trigger assembly could not duplicate the incident that was described. All parts tolerances and dimensions were found to be normal, including sear-connector engagement. Also, factory seals were intact on the trigger adjustment screws, indicating no alterations were made on the trigger outside our company. Trigger pull was well within our specifications at 4¹/₂ pounds.

Based on our findings, Remington Arms Company, Inc., cannot accept any liability or responsibility for the incident. It is possible that while your customer was moving the safety lever from the "safe" position to the "fire" position, the gun then discharged - as it is designed to do - because the trigger was being pulled with the gun no longer on "safe".

-1-