

Umm-80

MOD. 700

R* C1224

Seq No. 6259346

P.I. No.

Recd. 1-6-83

MFD. 7-69

Cleared By R. C. Johnson

NUMBER ✓

COMMENTS:

6-20-73

THIS GUN WAS COCKED, ITS SAFETY WAS SWITCHED TO THE "S" POSITION, AND IT WAS PLACED INSIDE A COLD BOX (INSIDE THERMOMETER INDICATED -30 F) AT 4:35 p.m. ON 06 APRIL 83.

(UPON REMOVAL OF THIS GUN FROM THE COLD BOX (INSIDE THERMOMETER INDICATED -29 F) AT 9:40 a.m. ON 07 APRIL 83, THE FOLLOWING TEST WAS IMMEDIATELY PERFORMED:

① Pull trigger to see if it binds or sticks back —
IT DID NEITHER.

② Switch safety to "F" position — IT DID NOT FIRE-DOWN.

③ Check bolt and check for ammo — NONE.

④ Check bolt and work safety — NO PROBLEM, POSITIVE ACTION.

⑤ Switch safety to "S" position, pull back hard on trigger, release trigger, switch safety to "F" position. Repeat this three times. — THE FIRING PIN DID NOT FIRE-DOWN.

⑥ With safety switched to "F" position, pull trigger. — THE FIRING PIN FIRED-DOWN. SNAPPY.

⑦ Rack the bolt and repeat the entire test. — No PROBLEMS ENCOUNTERED AND NO F.S.R. OBSERVED.

⑧ Perform "trick test". — GUN PASSED THE "TRICK TEST".