

CAL. 30.06 SPRG.

PROJECT #241095
TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START- RDS. FIRED	○ TOTAL RDS.
SW/JW/BL	11-4-00	PROOF STAMP + MAGNAFLUX STAMP ✓			
SW/JW/BL	11-4-00	HEAD SPACE			
SW/JW/BL	11-4-00	Trigger Pulls	(1) 4.50 (2) 4.75 (3) 4.75 AVERAGE 4.66		
SW/JW/BL	11-4-00	Indents	(1) .018 (2) .017 (3) .017 AVERAGE .0173		
SW/JW/BL	11-4-00	Bolt Stop function test	Locked position/unlocked bare hand OK gloved hand OK		
SW/PR	11-5-00	10 Rd Function Test	Remington Ammo R30064 Bolt real stiff to operate (PR/SW)	10	10
PKR	11-6-00	Returned to	Martinez to show the trigger is located to the left of center		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

BARBER - 5.22.06r0000961

37

ET06792

Confidential - Subject - 5.22 Protective Order - BARRY, 5.22.06 0000561

Subject: 5.2.2. Protective Order
BARBER - 5.2.2.061000561

R. 5.2.2. Protective Order

R. 5.2.2. Protective Order