

GUN # A-24

SERIAL # 7100 1224

CAL. 30.06 SPRG.

REMINGTON M/710

TRIAL and PILOT

DAILY TEST DATA SHEET

PROJECT #241095
TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JW/BL	11-4-00	PROOF STAMP & MAGNAGLUX STAMP ✓			
SW/JW/BL	11-4-00	HEAD SPACE	min .003		
SW/JW/BL	11-4-00	Load Safety function test	Remington Ammo R30064 (shot 10 rounds)	10	10
SW/JW/BL	11-4-00	HEAD SPACE	min .003		
Jesse/BL	11-5-00	POI Relative to POA		5	15
JA/BL	11-5-00	Trigger Pulls	(1) 5.0 (2) 4.5 (3) 4.5 AVERAGE 4.66		
JA/BL	11-5-00	Indents	(1) .019 (2) .018 (3) .018 AVERAGE .0183		
JA/BL	11-5-00	measurements	Sear Trigger Engagement (1) .0317 (2) .0323 (3) .0308 Average .0316		
			Sear Lift (1) .0126 (2) .0123 (3) .0118 Average .0122		
SW	11-5-00	Bolt Stop Function Test	OK Locked position / Unlocked position Bare Hand OK Gloved Hand OK		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

BARBER - 5.22.06r0000967

ET06798

Confidential - Subject: 52206r0000967 Order

Williams v. Remington