

CC: J. B. Maupin
S. M. Alvin
W. E. Seck) In turn
M. Walker)
H. J. Hackman) In turn
V. G. DeRous)
E. Sapp
J. W. Miller
R. Williamson

July 6, 1955

W. A. BEST

MODEL 722 - 308 CAL. PILOT LINE ACCURACY TEST

Accuracy testing of the 308 caliber has been completed, which in turn will comply with the functional test of April 29, 1955.

Procedure

1. Each gun was fired three five-shot groups from the shoulder, using a twenty power scope mounted on receiver and barrel.
2. Guns were cooled and cleaned between each group.
3. Ammunition used was Win. 180 gr. silver tip, Lot No. A63-11.
4. Lacking a bull gun at this time standardization of this lot could not be made.

The results are as follows:

#360962	Target 1.	2.2	#361581	Target 1.	2.7	#362768	Target 1.	1.9
	2.	2.55		2.	1.6		2.	2.6
	3.	2.8		3.	2.5		3.	1.5
	av.	2.5		av.	2.3		av.	2.0
#362831	Target 1.	2.9	#362206	Target 1.	2.5	#362751	Target 1.	1.9
	2.	2.2		2.	3.6		2.	1.2
	3.	1.8		3.	2.3		3.	1.9
	av.	2.3		av.	2.8		av.	1.7
#363848	Target 1.	1.4	#362496	Target 1.	3.0	#362881	Target 1.	3.2
	2.	2.3		2.	2.4		2.	2.7
	3.	2.8		3.	3.1		3.	2.4
	av.	2.2		av.	2.8		av.	2.8
#362897	Target 1.	3.0						
	2.	2.4						
	3.	2.7						
	av.	2.7						

It can be concluded that the accuracy of the Model 722 308 caliber is satisfactory.

C. J. Theriault
C. J. Theriault,