

Remington Confidential

TLW0010Q - Barrel Length:

Measure the length of the barrel. For the .30-06 and .270 caliber, the barrel length should be $22" \pm .125"$ measured from the bolt face to the end of the muzzle. ($24" \pm .125"$ for Magnum caliber)

Method:

- Check firearm for live ammunition
- Close bolt over and empty chamber
- With the butt of the rifle on the floor and the muzzle pointing up, carefully and gently, so as to not scratch the bore or nick the rifling, insert a brass rod (not steel) into the muzzle of the rifle until it stops on the bolt face. Move the brass rod around to insure that you are on the bolt face and not on the edge of the ejector or extractor.
- Carefully mark the brass rod where it is even with the edge of the muzzle
- Remove the rod and measure the length.

Data Required:

- Rifle serial number
- Measurement of barrel lengths in inches.

TLW0010R - Length of Pull:

Length of Pull – the distance from the center of the butt plate (from center of top (i.e. heel) to center of bottom (i.e. toe)), to the inside curve of the trigger. Measurements are taken for information only.

Method:

- With muzzle of rifle pointed down and barrel clamped securely in holding device
- Located the center of the distance, top to bottom of the butt pad and mark pad or butt plate
- Measure to the inside curve of the trigger (at the front)

Data Required:

- Rifle serial number
- Length of Pull measurements