

Competitive Product Evaluation
Winchester Low-Priced Bolt Action
Center Fire Rifles

LIMITED DISTRIBUTION

Remington 700ADL

Winchester 770

Trigger Guard

type:	both for blind magazine, no provision for floor plate	
material:	aluminum alloy	aluminum alloy
coloring process:	anodized	anodized (relatively soft) and black enameled
surface finish:	smooth and uniform, moderate gloss, sanding marks visible on interior of bow	somewhat coarse, very slight gloss, sanding marks visible on interior of bow
contour:	width varies on blending radii	width is a straight taper from top to bottom (die draft perhaps)

Sights

front:	cross-serrated face ramp, flat faced gold bead front sight, dovetail mounted to base; detachable	longitudinally-serrated face ramp, convex faced silver bead front sight, dovetail mounted to base; hooded; detachable
rear:	ramp-mounted, elevation governed by means of a sight step, discrete incremental changes; windage changes screw adjustable; U-notch, flat top leaf; detachable	Williams "guide" rear sight, windage and elevation on independent dovetails, no discrete adjustments, index scale provided; semi-buck horn U-notch leaf; detachable
elevation range, inches @ 100 yds.:	13.1"	20.7"
sight radius:	16-1/2"	14-3/4"