

DON'T SAY IT—WRITE IT

TO GEORGE MARTIN

FROM GENE BULLIN

SAFETY MALFUNCTIONS GALLERY

DATE 5-2-75

MODEL	MALFUNCTIONS												TOTAL SAFETY MALFUNCTIONS BY MODEL			
	FSR			JO			FD			FOS				SWW		
	705	74	75	705	74	75	705	74	75	705	74	75		705	74	75
40							4									4
1P 100							3									3
540																
541								2	1							3
580													1			1
581							3	2	1							6
582																
100	1						10	74	55							140
700	9						7	19	10	1				1		47
788	4						3	9	3	2	9	4	14	95	53	196
ARLY MALF. TOTALS	14						30	106	70	3	9	4	14	97	53	400

TOTAL SAFETY MAL.

MALFUNCTION MEANINGS

FSR - FIRES WHEN SAFE IS RELEASED - SELF EXPL.

JO - JARS OFF (HAMMER FAILS TO STAY ENGAGED WITH SEAR AND FALLS DOWN WHEN GUN IS JARRED.)

FD - FOLLOWS DOWN (COCKING PIECE FAILS TO PROPERLY ENGAGE WITH SEAR AND FOLLOWS THE COCKING CAM SURFACE OF THE BOLT TO THE FIRED POSITION).

FOS - FIRES ON SAFE (GUN FIRES WITH SAFE IN "ON" POSITION WHEN TRIGGER IS PULLED).

SWW - SAFETY WON'T WORK - SELF EXPL.

* - 1975 DATA FROM DEC. 26, 1974 TO APRIL 29, 1975 ONLY.