REMINGTON ARMS COMPANY, INC.

Remington OFFIRD

"CONFINE YOUR LETTER TO ONE SUBJECT ONLY"_

January 30, 1979

XP-100 FIRE CONTROL MODIFICATION TEST PROGRAM January 29, 1979 Meas./Test Lab

I. MEASURE TEST SAMPLES FOR FOLLOWING:

- a. Headspace, indent & trigger pull
- b. Safe On and Safe Off forces
- c. Safety function test
- d. Sear engagement
- e. Sear lift
- f. Recoil lug movement during live firing

II. DRY CYCLE TEST - TWO XP-100 PISTOLS

- 50,000 Safe On Safe Off dry cycle with lubrication
 Followed by 10,000 cock and dry cycles with lubrication
 Record following in every 10,000 cycles
- - 1. Safe On Safe Off forces
 - 2. Safety function test
 - 3. Trigger pull
 - 4. Sear engagement and lift

XP-100 FIRE CONTROL MODICIATION TEST PROGRAM

Jan. 30, 1979

III. LIVE FIRING TEST - FIVE XP-100 PISTOLS:

- a. Five to 500 rounds (fixture and/or stock)
- b. Measure and check "I" items
- c. Three on to 1000 rounds
- d. Measure and check "I" items
- e. One on to 2000 rounds 2 500P05.
- f. Measure and check "I" items
- IV. DROP TEST TWO XP-100 PISTOLS (+control):

 - a. Determine if modifications effect drop test performance.b. Use pendulum, hard maple impact media, Safe On and Safe Offc. Suggest start at three foot drop
- V. ITEMS LOOKING FOR:
 - a. Trigger upset or deformation due to modification
 - b. Stable sear lift, sear engagement, trigger pull
 - c. Reliable safety performance
- VI. AMMUNITION AVAILABILITY:

R & D - 0 rds.Plant Gallery - 7000 rds. Order placed 1/29/79 for 5000 rds.