

After 1,000 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

4

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A 6745544

Headspace as Received: M +.002

Safe - "ON" - I. 7.5

"OFF" - I. 5.0

Proof: OK

(6.8) 2. 7.0
3. 6.0

(5.2) 2. 5.0
3. 5.5

Headspace after Proof: _____

Firing Pin Indent(in.)

(0.2) 1. .022
2. .022
3. .022

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

(4.0) 1. 4.0
2. 4.0
3. 4.0

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82