

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE

Remington  
RECEIVED

PETERS  
RECEIVED

Distribution:

"CONFINE YOUR LETTER TO ONE SUBJECT ONLY" \_\_\_\_\_

RESEARCH TEST and MEASUREMENT REPORT - Report No: 840321

TEST TITLE: "RESULTS ONLY"

M/700 VENDOR SUPPLIED CONNECTORS VS. CONNECTORS  
TO MODEL DRAWING.

Prepared by: R. W. HOWE

Date Prepared: FEB. 28 1984

Proofread and Cleared By:

R.E. Nightingale,  
Foreman-Test Lab / Foreman-Measurement Lab

Signature \_\_\_\_\_

Date \_\_\_\_\_

C.E. Ritchie,  
Sr. Supervisor - Testing,  
Meas. & Mech. Analysis Lab

Signature \_\_\_\_\_

Date \_\_\_\_\_

REMINGTON ARMS Co. Inc.  
FIREARMS RESEARCH DIVISION,  
FEB 28, 1984

REPORT #840321

TO: R. NIGHTINGALE

TEST TITLE: "RESULTS ONLY"  
M/700 VENDOR SUPPLIED CONNECTORS VS. CONNECTORS  
TO MODEL DRAWING.

REASON FOR TEST:

TO DETERMINE IF THERE IS A FUNCTIONAL  
DIFFERENCE IN THE VENDOR SUPPLIED CONNECTORS  
AND CONNECTORS THAT ARE TO MODEL DRAWING.

TEST PROCEDURE:

SIXTY FOUR M/700 FIRE CONTROLS WERE ASSEMBLED  
INTO M/700 ACTIONS, TEN AT A TIME, AND PENDULUM  
DROP TESTED AT THE 2' AND 4' LEVELS IN BOTH  
SAFE "ON" AND SAFE "OFF" MODES IN THE FOLLOWING SIX  
POSITIONS. MUZZLE FIRST, BUTT FIRST, TOP SIDE, BOTTOM  
SIDE, RIGHT SIDE, AND LEFT SIDE. ONE DROP FOR EACH  
MODE AND POSITION AT EACH DROP LEVEL AS REQUESTED  
BY J.A. LAWRENCE, [REDACTED] CURRENT PRODUCTS DESIGN.

TEST RESULTS:

TEST RESULTS ARE IN THE FOLLOWING PENDULUM DROP  
TEST DATA SHEETS. TO BE EVALUATED BY CURRENT  
PRODUCTS DESIGN.