

MDK  
08/09/93

NBAR FEATURES:

RECBAR:

1. INTERGAL BARREL AND RECEIVER
2. FORGED BARREL AND RECEIVER
3. 5R RIFLING
4. FORWARD LOCKING, THREE LUG  
(67 DEG. BOLT ROT.)
5. ACTION LENGTH .5" SHORTER THAN M/700  
(RIGID)
6. GREATER LOCKING STRENGTH THAN M/700  
(BEARING AND SHEAR AREA)
7. COMMON BARREL CONTOUR (MAG AND REG)
8. DETACHABLE MAG. BOX, STAGGERED BOX/INLINE FEED
9. COMMON SCOPE MOUNTING SURFACES
10. REMINGTON ONE PIECE SCOPE MOUNTS RADIALY FASTENED  
TO RECEIVER

BOLT ASSEMBLY:

1. ENCLOSED BOLT SHROUD
2. CLAW EXTRACTOR
3. COCKING INDICATOR
4. ENCLOSED BOLT PLUG ??????
5. FIELD STRIPPABLE

TRIGGER ASSEMBLY:

1. TWO POSITION SAFETY WITH RELEASABLE BOLT LOCK
2. CUSTOMER ADJUSTABLE TRIGGER FULL ABOVE SAFE LIMIT
3. WIDE TRIGGER

STOCK ASSEMBLY:

1. ALUMINUM RECOIL/BEDDING INSERT EPOXIED OR MOLDED INTO STOCK  
(FRONT AND REAR ALUMINUM BEDDING)
2. FUTURISTIC SYNTHETIC STOCK WITH INSERTABLE PADS
3. CLASSIC WALNUT STOCK

LOCK TIME :

~~30%~~ <sup>30%</sup> REDUCTION IN LOCK TIME FROM m/700  
(3.0 ms → 2.1 ms)

5-10% QUICKER THAN m/788 (788 = 2.3 ms)

↳ that is for long action !!  
↳ short action NBAR possibly under 2 ms