

ENGINEERING DESIGN

10.15.93
WAW
POINT OF VIEW

HIGH

- SHORT DIMENSIONS PARALLEL TO CEBL
- AVOID ANY REASON TO PUT FINGER WITHIN TRIGGER GUARD EXCEPT TO INTENTIONALLY FIRE
- EASY TO UNDERSTAND - HIGHLY INTUITIVE OPERATION
- REALITY VS. PERCEPTION RECONCILED THRU ACTUAL TESTING / PERFORMANCE
- PRESERVE ADVANTAGES OF RESILIENT (CONNECTOR) FUNCTION
- DO NOT USE SEAR AS BOLT STOP OR APPLY BOLT STOP IMPACT TO ASSEMBLY

• REDUCED LOCK TIME

- ACTUATE SAFETY WITH BOLT OPEN

MEDIUM

- QUIET OPERATION
- ENHANCED CORROSION RESISTANCE
- COMPEL TRIGGER TO SUPPORT POSITION IN MOVING SAFETY F → S
- FULL TRIGGER RETRACTION UPON PARTIAL PULL
- MEANS TO PREVENT INCORRECT ASSEMBLY / RE-ASSEMBLY OF COMPONENTS

AS AMENDED
AT MEETING
10.15.93.

~~DSF HAS
ORIGINALS OF
AMENDED
VERSION.~~