SKA-3777 DEG. BY DATE DATE PARTY CHK. BY DATE APP. BY DATE TIYLE DIN						DO NOT SCALE THIS DRAWING: WORK TO FIGURES UNLESS OTHERWISE NOTED. TOLERANCES ON DECIMAL DIMENSIONS ARE; 1 PLACE (.1) — TOLERANCE ± .015 2 PLACE (.01) — TOLERANCE ± .010 3 PLACE (.001) — TOLERANCE ± .005	RECOMMENDED MATERIAL AND HEAT TREAT MATERIAL MANUFUT S SPEC. HEAT TREAT
A-	REMINGTON ARMS CO. INC.			D. INC.	& ON FRACTIONAL DIMENSIONS ± 1/64 DON ANGULAR DIMENSIONS ± 00°—30' FINISNES ARE DESIGNATED BY ROOT MEAN SQUARE (R. M. S.) MICRO-INCH ROUGHNESS VALUES AND ARE THE MAXIMUM ROUGHNESS ACCEPTABLE, UNLESS OTHERWISE SPECIFIED.	HARDNESS COLOR HEAT TREAT AND COLOR TO BE DONE BY REMINGTON	
nga	PART NO.	PART USI POLI LICK P RETAINING	7.006	EK		THIS DRAWING OR INFORMATION IS PROPRIETARY INFORMATION TO THE REMINGTON ARMS COMPANY, INC.	
						.375	1
			T	T			OGZ DIG. LIGHT DUTV
							ROLL PIN OR EQUIVALENT
ALT.	W	/A.B	NEF.	••	DATE		
FORM IFA	NEV. 280 H H.S.	ALTERATIONS	\bigvee	\bigvee	\bigvee		