EXHIBIT "E"

REMINGTON ARMS COMPANY, INC.

R0-48 REV. 4-54

INTER-DEPARTMENTAL CORRESPONDENCE

Remington CMD

September 18, 1981

TO: PRODUCT SAFETY COMMITTEE

FROM: T. W. RAWSON

SUBJECT: 270 WIN. PROOF AND PRODUCTION ROLL MARK COMMENTS

Ilion recently returned 21M - 270 Win. proof loads to Leboke with a complaint of high pressure. The following list of 5 lots shows the detail of pressures measured in subsequent test. R30C 92000 4/81 R01K 83500 - F/81

R30C	92000	4/81	
RO1K	83500	5/81	100
R05K	79500	5/81	E.
R12I	96500	3/81	Υς. Έλλ
N12U	104500	3/80	
1.000 (19) 1.000 (19)	Vile Contraction	. St. St.	

These pressures represent highest individual shot (C.U.P.). Three loads exceed SAAMI. The SAAMI specification for max individual pressure is 85800.

DuPont 198 is loaded in these cartridges and is believed responsible for the pressure spike.

Five cases of ROLK and RO5K represent the current warehouse inventory and are under hold. No other inventory is available and Ilron has been using handloads to proof 270 Win. chambered mifles. Ilion also reports similar problems with a subsequently purchased quantity of Winchester product.

A recall of this product is recommended.

TWR/Y

e^{stein}te