

TLW 0300 A0

Project No. 241045

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Gun
Firecontrol No. C30 Firecontrol Type: Std. Date: 12-10-00
Dry Cycles/Rounds Completed: Stock Type Syn Engagement at Start 0209
Model No. 710 Serial No. 71001744 Engagement at End 0208
Trigger Pull at Start of Test (1) 4.75 (2) 4.5 (3) 4.5 (4) 4.5 (5) 4.75 (6) 4.75
Average Trigger Pull at Start of Test: 4.62 Std. Dev. of Trigger Pull at Start of Test:
Trigger Pull at End of Test (1) 4.5 (2) 4.5 (3) 5.0 (4) 4.5 (5) 4.75 (6) 4.5
Average Trigger Pull at End of Test: 4.62 Std. Dev. of Trigger Pull at End of Test:

Tester Initials: JW + SW

Additional Notes and Comments

W/O Scope

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.3-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
12-10-00 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
Chamber, Magazine loaded to capacity with Dummy Rounds.
After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Notes for Firearms with the ISS system installed - The ISS will be set in the unlocked
position for all six orientations of the Jar-Off Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

ET07696

TLW 0300AN

Project No. 241095

C 30

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST*SAAMI Specifications for Standard Drop Test:*

Drop Test: 48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
 12/11/00 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	83
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	bolt handle broke bolt stop
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	Replaced bolt handle with released
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	one from gun B2 headspace mint
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	bolt stop released 1002

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall TLW0300AP
 12/10/00 Drop - onto 1" thick 85 durameter (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials SW/JW

Page 2 of 2
 Z101\DROPTEST_REV3.DOC

ET07697