TLW 03/9
Project No. 24/095

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

SAAMI Specifications for Standard Drop Test:

Drop Test:

48-inch drop - onto 1" thick 85 durameter (Shore A) Rubber Matt Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case in Chamber, Magazine loaded to capacity with Dummy Rounds. After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the

ISS system in the	unlocked position for all six	orientations of the Drop Test
Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	PassFail	
Barrel Vertical, Muzzle Down:	Pass Fail	
Barrel Horizontal, Left side of Stock	t Up: Pass V Fail	
Barrel Horizontal, Right side of Sto	ck Up: Pass Fail	
Barrel Horizontal, Bottom of Stock	Up: Pass Fail	
Barrel Horizontal, Bottom of Stock	Down: Pass Fail	
SAAMI Specifications	for Standard Rotation Test:	· · · · · · · · · · · · · · · · · · ·
Pro Fire In C After "Rotation Te <u>Note: for Firearms</u> <u>ISS system in the</u>	hamber, Magazine loaded to concept the concept of the Primed Case st" (safety in "Safe" position) with the ISS system installed uplocked position for both or supposed the concept of the ISS system installed uplocked position for both or supposed the concept of	(Shore A) Rubber Matt 'Safe" position, Fresh Primed Case apacity with Dummy Rounds. to verify firearm will still function. - one drop per orientation. - The Firearms will be set with the ientations of the Rotation Test.
Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side	of Stock is Up: Pass Va	íil
Firearm Vertical, Drop so right side	of Stock is Up: Pass Fail	!
Notes: (continue on back of sheet if nece	ssary)	
		Tester's Initials JTQ
		Page 2 of 2 Z101\DROPTEST_REV3 DOC

ET08271