

CONFIDENTIAL

Test Lab Report  
TLW 9142F

ET09488

# Test Lab Work Request Form

<b>Date Submitted:</b> 19 May, 1999	<b>Tracking #:</b> TLW 9142F
<b>Project #:</b> 241095	<b>Engineer:</b> SNEDEKER, J.R.
<b>Test Objective:</b> <b>COMPLETE STANDARD PROOF TEST ON M/710 EET SAMPLE RIFLES</b> <b>SUBMITTED FOR EVALUATION ON 18 MAY '99.</b>	
<b>Test Description:</b>  <ol style="list-style-type: none"> <li>1. Measure and record Head-space both before and after 1 .30-06 Cal. Proof round is fired in sample rifles.</li> <li>2. Use lanyard and use extreme caution, comply with all safety procedures used when proofing firearms.</li> <li>3. After firing proof round examine rifle for any signs of damage especially in the chamber area, on the bolt lugs, bolt face, extractor, or ejector. Examine locking lug area in the barrel/receiver area for any indication of cracking or swelling of material. Note anything of an unusual nature. Check the firing pins for damage to the tip or for any indication of set-back due to high pressure.</li> <li>4. For each of the rifles that pass this proof test, imprint with proof stamp on the right side of the barrel at the chamber location.</li> </ol>	
<b>Resource Usage:</b> <b>Manpower Requirements -</b> <b>1 technician</b> <b>Facility Requirements -</b>	<b>Test Results Required:</b> <b>Formal Report: Data Only: X</b> <b>REQUESTED Completion Date:</b> <b>28 May '99</b>
<b>Required Materials/Parts/Equipment (include quantities):</b> <b>Graduated Head-space gauges for .30-06 caliber,</b> <b>Proof Stamp</b>	
<b>Test Parts Availability Date:</b> 18 May '99	
<b>Start Date:</b> 5-19-99 <b>Completion Date:</b> 5-19-99 <b>Report Date:</b>	<b>Test Assigned To:</b> Jeff Wade <b>5/19/99</b>

☐ INDEXED
 ☐ ASSIGNED
 ☐ SCHEDULED

ET09489