

TLW 0010AU

Project No. 241095

EXTENDED ROTATION TEST

Gun
 Model No. B-30 Firecontrol Type: Standard Date: 9-29-00
 Dry Cycles/Rounds Completed: _____ Stock Type Syn Engagement at Start .0244
 Model No. 710 Serial No. 71001302 Engagement at End .0262
 Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____
 Average Trigger Pull at Start of Test: 4.75 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 3.5 (2) 3.5 (3) 4.0 (4) 4.0 (5) 4.25 (6) 4.0
 Average Trigger Pull at End of Test: 3.875 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: SW/JW

Additional Notes and Comments

Gun with scope**SAAMI Specifications for Standard Rotation Test do not apply to this test.**

Extended Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto Tile Floor backed by Concrete. NO RUBBER MATT
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

**Note: for Firearms with the ISS system installed - The Firearms will be set with the
 ISS system in the unlocked position for both orientations of the Rotation Test.**

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	

Notes: (continue on back of sheet if necessary)

Tester's Initials _____