

TLW 91241Project No. 27095

Page 1 of 2

S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST

Firecontrol No. _____ Firecontrol Type: _____ Date: 6/16/99Dry Cycles/Rounds Completed: _____ Stock Type Syn Engagement at Start _____Model No. M/710 Serial No. XC-1054 Engagement at End _____

Trigger Pull at Start of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____ 83

Average Trigger Pull at Start of Test: _____ Std. Dev. of Trigger Pull at Start of Test: _____

Trigger Pull at End of Test (1) _____ (2) _____ (3) _____ (4) _____ (5) _____ (6) _____

Average Trigger Pull at End of Test: _____ Std. Dev. of Trigger Pull at End of Test: _____

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12 inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Comments

Barrel Horizontal, Bottom of Stock Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	Seam retaining pin came out
Barrel Horizontal, Bottom of Stock Up :	Pass <input type="checkbox"/>	Fail <input checked="" type="checkbox"/>	Fired Primed case
Barrel Horizontal, Left side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Horizontal, Right side of Stock Up :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	
Barrel Vertical, Muzzle Up :	Pass <input checked="" type="checkbox"/>	Fail <input checked="" type="checkbox"/>	
Barrel Vertical, Muzzle Down :	Pass <input checked="" type="checkbox"/>	Fail <input type="checkbox"/>	

ET19753