

GUN # A-8

M/710 MAGNUM TRIAL PILOT TEST

TRACKING # TLW 1303

SERIAL # 71146992

PROJECT # 241314

CAL: 300 WIN MAG

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS	AT START-0
				RDS. FIRED	TOTAL RDS.
SW/PR	12/19/03	Out of box Inspection	TWL1303A		
JS	12/22/03	De-torque Scope Cross Bolt screws	Front 25in Lb Rear 27in Lb		
DL	12/22/03	Headspace	min. .004		
BL	12/22/03	PROOF	Tight Opening	1	1
BL	12/22/03	Headspace	min. .004		
JL/BL	12/22/03	Depth front Take down Screw hole			
BL	12/22/03	Firing Pin Indent	.020-.020-.019 Avg. .0196		
JS	12-29-03	Rear/Trigger Engagement	Arg. .0312		
JS	12-29-03	Rear 1st	.0149		
SW/JS	1-13-04	Change out Bolt Head			
SW/JS	1-13-04	Headspace Min +.006			
SW/JS	1/13/04	PROOF RCL		1	2
SW/JS	1/13/04	Headspace after proof	Min +.007		
SW	1/14/04	200 Rd Basic Jct Function Test		200	202
SW/RL	1/18/04	Headspace Min +.006			
JR	1-16-04	Shoulder function test X 20 Rds. Bolt difficult to close; Bolt hangs up on the shell feeding.		20	222
JS/BL	1-19-04	Clean & Inspect	See Inspection Sheet Broken extractor		

Logform

BARBER - 5.22.06-0003743

Confidential - Submitter to 2206060003743 Order Williams V. Remington

ET20122

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Trial & Pilot Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-B

TLW #: TLW1303

Date: 01 1 19 04Inspector: JS/BCRound Level: 222☒ Measure Headspace min +.006☒ Sear Engagement: 1st. .0316 2nd. .0316 3rd. .0305Ave. .0312 spec. .020" to .025"☒ Trigger Pull: 1st. 5.033 2nd. 4.728 3rd. 4.139Ave. 4.633 spec- 4 lb. to 5.5 lb.☒ Check Take-Down Screws and Re-tighten if necessary.☒ Inspect extractor & bolt face area. Bolt face extractor☒ Inspect cam surface, locking lugs and bolt stop for signs of excessivewear: locking lugs some wear, bolt stop some wear☐ Inspect stock for any signs of cracking or other

failure.

☒ Other items ofnote: magazine Box is protruding / receiver insert has a defect must
be in mold.

TLW1303

Remington Confidential

ET20123