

CAL: 300 WIN MAG

PROJECT # 241314

BARBER - 5.22.06r0003759

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-0	
				RDS. FIRED	TOTAL RDS.
SW/PR	12/19/03	Out of box Inspection	TLW1303A		
JS	12-22-03	Detonate - Scope Crossbolt Screws	Front 17 Rear 25		
BL	12-22-03	Headspace	min +.005		
BL	12-22-03	Proof	OK	1	1
BL	12-22-03	Headspace	min +.005		
JS/BL	12-22-03	Depth Front Take down Screw hole			
BL	12-23-03	Firing Pin Idents	.020-.021-.021 Avg. .0206		
JS	12-29-03	Gear/Trigger Engagement	Avg. .0304		
JS	12-29-03	Gear Lift	.014		
SW/JS	1-13-04	Charge out Bolt Head			
SW/JS	1-13-04	Headspace Min +.005			
SW/JS	1/13/04	Proof & Rd		1	2
SW/JS	1/13/04	Headspace after proof	Min +.006		
JS	1-15-04	2nd Jack Function	1st Bolt hard to close on Rds 121-140	200	202
SW	1-15-04	Headspace Min +.006	(All Take down screws were loose)		
BL	1-16-04	Shoulder fire	Bolt Hard to close	20	222
JS/BL	1-19-04	Clean & Inspect	See Inspection Sheet		

Logform

Confidential - SHARPER - 027000057592 Order

ET20138

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Trial & Pilot Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-16

TLW #: TLW1303

Date: 01 1 19 1 04Inspector: J. BL

Round Level: _____

☒ Measure Headspace min + .005☒ Sear Engagement: 1st .0291 2nd .0304 3rd .0283Ave. .0292 spec. .028" to .025"☒ Trigger Pull: 1st 4.556 2nd 4.485 3rd 4.507Ave. 4.516 spec. 4 lb. to 5.5 lb.☒ Check Take-Down Screws and Re-tighten if necessary.☒ Inspect extractor & bolt face area. Bolt face has some wear☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs - Bolt stop worn☒ Inspect stock for any signs of cracking or other failure.☒ Other items ofnote: magazine Box protruding

TLW1303

Remington Confidential

ET20139