

CAL: 300 WIN MAG

TRACKING # TLW 1303
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS	AT START-0
				RDS. FIRED	TOTAL RDS.
SW/PR	12/19/03	Out of box Inspection			
JS	12-22-03	Distance - Stem Crosshairs	Screen Front 40 Rcar 40		
BL	12-22-03	Headspace	Min + .003		
BL	12-22-03	Proof	OK	1	1
BL	12-22-03	Headspace	Min + .003		
JS/BL	12-22-03	Depth Front Take down	Screws hole		
BL	12-28-03	firing Pin Indent	.018-.019-.019 Avg. .0186		
JS	12-29-03	Gear/Trigger Engagement	Arg. .0298		
JS	12-29-03	Gear Lift	.0154		
SW/JS	1/13/04	Change out bolt head			
SW/JS	1/13/04	Head spacer	Min + .004		
SW/JS	1/13/04	Proof	Rel	1	2
SW/JS	1/13/04	Head spacer	After proof Min + .004		
SW	1/15/04	300 Rd Basic Jch Function Test		200	202
SW	1-15-04	Headspace	Min + .004 (Center Takedown screw loose)		
BL	1-16-04	Shoulder Fine	ok	20	222
JS/BL	1-20-04	Clean & Inspect	see Inspection sheet		

Logform

Q

BARBER - 5.22.06r0003783

ET20162

Confidential - ~~Subpoena~~ Order
 DATED 10.27.2018
 Williams v. Remington

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Trial & Pilot Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-30

TLW #: TLW1303

Date: 01 120 104Inspector: JS/BLRound Level: 222☒ Measure Headspace min t. 004☒ Sear Engagement: 1st. 0292 2nd. 0279 3rd. 0277Ave. 0282 spec- .020" to .025" Rest Eng☒ Trigger Pull: 1st. 4.801 2nd. 4.858 3rd. 4.733Ave. 4.791 spec- 4 lb. to 5.5 lb. 0241☒ Check Take-Down Screws and Re-tighten if necessary.☒ Inspect extractor & bolt face area. some wear on bolt face☒ Inspect cam surface, locking lugs and bolt stop for signs of excessivewear: Locking lugs some wear, bolt stop worn☒ Inspect stock for any signs of cracking or other failure.☒ Other items ofnote: magazine Box protruding

TLW1303

Remington Confidential

ET20163