

C6649119

MODEL 700™ M24

Model S&S™

Action

Barrel Length

Capacity

Order No. 5716

*Includes 1 in chamber.

Remington

Remington
MODEL 700TM H24

VERY IMPORTANT:
 Instruction Book
 enclosed to assure
 safe use of this
 firearm.


DU PONT
 REG. U.S. PAT. & TM. OFF.

SERIAL NO.
 C6649119


ORDER NO.
5716

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat. & Tm. Off. Marca Registrada Marca Deposee.

20



UPC



MOD. _____ GA. _____ GUN # 9119
 CAL. _____ # _____

# TEST	DATE	MALFUNCTION/DEFECT	ASSEM. #
	1st		
NF	8/13	Shaver Brass	KS
	2nd		
	8/14	Polish face of Bolt	
	91	100 Rd Test	RW
	3rd		
	4th		
		FUNCTION	RD 6654 Rev 1

TEST INIT. ACTION TO CORRECT		ASSEM. #
PROOF	<i>shot OK</i> <i>test</i> <i>8-14-91 AH</i>	
TEST		
TGT		
PROOF		
TEST		
TGT		
PROOF	ENGINEER	
TEST		
TGT		
PROOF	ENGINEER	
TEST		
TGT		

CONTRACT # DAAA21-87-C-0086

GUN SERIAL #

C6649119

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock		6/27/91	KA
600	Proof		6/27/91	KA
607	Check Headspace		6/27/91	KA
610	Dis-assemble Gun		6/27/91	KA
612	Magnaflux Barrel Action		JUL 1 8 1991	CS
	Magnaflux Bolt		JUL 1 8 1991	CS
615	Rollmark Caliber		JUL 1 8 1991	CS
617	Drill and Tap Sight Holes		JUL 1 8 1991	FB
618	Polish Barrel		JUL 2 0 1991	WB
620	Apply Coatings (Barrel Action)		7-7-91	KA
	Apply Coating (Bolt)			KA
625	Final Assembly A) Clean inside of Bolt Assembly		8/8/91	KA
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head		8/8/91	KA
	C) Inspect Ejector Hole for Chamfer		8/8/91	KA
	D) Oil Firing Pin Ass'y		8/8/91	KA
	E) Adjust Trigger Pull to Min Setting and Stake		8-9-91	KA

op. #	UP. NAME BARBER, M24 0065033	READINGS					DATE	INIT
625 cont.	F) Safety On Force	6	6	6			8-9-91	JK
	G) Safety Off Force	4	4	4			8-9-91	JK
	H) Trigger Pull Test & Retainability						8-9-91	JK
	I) Firing Pin Indent	.0215	.022	.022			8-9-91	JK
	J) Assemble Stock						8-12-91	JK
	K) Assemble Swivel Studs						8-14-91	D/H
	L) Attach Front and Rear Sight Assemblies						8-12-91	JK
	M) Iron Sight Alignment						8-12-91	JK
	N) Detach Front & Rear Sights & place in numbered container						8-12-91	JK
	O) Attach Scope to Rifle						8-12-91	JK
	P) Detach & Attach Scope 20 Times						8-12-91	JK
640	Gallery Target & Test						8-13-91	NF
	A) Time						"	NF
	B) Malfunctions						"	NF
	C) Pierced Primers						"	NF
	D) Optical Clarity of Scope						"	NF
645	Inspect for Live Ammo						8-13-91	NF
655	Final Inspection							
	A) Headspace						8-14-91	D/H
	B) Trigger Pull	2.61	2.69	2.39	2.67	2.66	8-14-91	JK
	C) Function						8-14-91	D/H
660	Pack						9-19-91	NF

CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # C6649119
23 Aug 1991

CENTROIDAL DISTANCES

0 TO	1	.101237
1 TO	2	.272738
1 TO	3	.279501
1 TO	4	.189652
1 TO	5	.153447

4 <----POA


THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.1038
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0374
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .110332
THE AMR FOR THIS RIFLE IS: .8268

23 Aug 1991

FILE:/PATTERNING/CENTERFIRE_PATT/06649113

CENTERFIRE PATTERNS

2



OF SHOTS = 10

IN CIR

1in = 5

2in = 6

3in = 9

IS = 2.787

VS = 2.234

GS = 2.787


CENTROID #

PATTERN #	10	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.178	.999	1.024
MINIMUM X	-1.689	-.859	-.834
MAXIMUM Y	.888	.832	.656
MINIMUM Y	-1.346	-1.402	-1.776
CENTROID X	-.191	-.012	-.037
CENTROID Y	.052	.108	.284
POR TO CENTROID in.	.198	.109	.286
MIN RADIUS	.062	.161	.289
MEAN RADIUS	.046	.749	.651
MAX RADIUS	1.607	1.417	1.285
HORIZONTAL SPREAD	2.787	1.858	1.958
VERTICAL SPREAD	2.234	2.234	1.432
EXTREME SPREAD	2.787	2.256	1.984
NUMBER IN ONE INCH CIRCLE =		3	
NUMBER IN TWO INCH CIRCLE =		6	
NUMBER IN THREE INCH CIRCLE =		9	

23 Aug 1991

FILE:/PATTERNING/CENTERFIRE_PATT/08B49119

CENTERFIRE PATTERNS # 3



OF SHOTS = 10

IN CIR

1in = 1

2in = 7

3in = 9

HE = 1.883

VS = 2.345


GS = 2.500

PATTERN #	10	9	8
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.732	.889	.662
MINIMUM X	-1.251	-1.174	-.815
MAXIMUM Y	.821	.652	.606
MINIMUM Y	-1.524	-.883	-.929
CENTROID X	-.221	-.298	-.151
CENTROID Y	-.193	-.024	.022
POA TO CENTROID in.	.294	.299	.152
MIN RADIUS	.283	.136	.283
MEAN RADIUS	.917	.801	.728
MAX RADIUS	1.671	1.232	1.192
HORIZONTAL SPREAD	1.983	1.983	1.477
VERTICAL SPREAD	2.345	1.535	1.535
EXTREME SPREAD	2.500	2.123	2.000
NUMBER IN ONE INCH CIRCLE =	1		
NUMBER IN TWO INCH CIRCLE =	7		
NUMBER IN THREE INCH CIRCLE =	9		

22 Aug 1991

FILE:/PATTERNING/CENTERFIRE_PATT/C6845113

CENTERFIRE PATTERNS # 4



OF SHOTS = 10

IN CIR

1 in = 3

2 in = 7

3 in = 10

HS = 2.436

VS = 1.572

GS = 2.583

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.154	.823	.679
MINIMUM X	-1.282	-1.154	-1.069
MAXIMUM Y	.768	.679	.675
MINIMUM Y	-.804	-.729	-.735
CENTROID X	-.048	-.176	-.032
CENTROID Y	.075	.164	.168
POA TO CENTROID in.	.089	.241	.171
MIN RADIUS	.400	.342	.346
MEAN RADIUS	.818	.749	.672
MAX RADIUS	1.406	1.154	1.089
HORIZONTAL SPREAD	2.436	1.977	1.748
VERTICAL SPREAD	1.572	1.408	1.408
EXTREME SPREAD	2.583	2.045	1.784
NUMBER IN ONE INCH CIRCLE =	3		
NUMBER IN TWO INCH CIRCLE =	7		
NUMBER IN THREE INCH CIRCLE =	10		

23 Aug 1991

FILE:/PATTERNING/CENTERFIRE_PATT/08849119

CENTERFIRE PATTERNS # 5

POA

1in circle

2in circle

3in circle

CENTROID *

OF SHOTS- 10

IN CIR

1in = 1

2in = 5

3in = 10

HS= 2.198

VS= 1.897

GS= 2.515

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.142	.965	.966
MINIMUM X	-1.056	-.929	-.928
MAXIMUM Y	.718	.794	.644
MINIMUM Y	-1.279	-1.203	-1.122
CENTROID X	-.099	-.226	-.227
CENTROID Y	-.028	-.104	.046
POA TO CENTROID in.	.102	.249	.231
MIN RADIUS	.137	.095	.218
MEAN RADIUS	.832	.831	.777
MAX RADIUS	1.334	1.222	1.249
HORIZONTAL SPREAD	2.198	1.894	1.894
VERTICAL SPREAD	1.997	1.997	1.766
EXTREME SPREAD	2.515	2.205	1.981
NUMBER IN ONE INCH CIRCLE =	1		
NUMBER IN TWO INCH CIRCLE =	5		
NUMBER IN THREE INCH CIRCLE =	10		

SWS TRIGGER PULL TESTAVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C-6649119DATE 8-9-91TESTER JU

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.65	2.61	2.38	2.61	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.68	2.44	2.40	2.69	
PULL #3	2.56	2.43	2.49	2.39	
PULL #4	2.68	2.40	2.44	2.67	
PULL #5	2.69	2.44	2.40	2.66	
TOTAL					
AVG.					

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.50	3.43		
PULL #2	3.55	3.39		
PULL #3	3.53	3.38		
PULL #4	3.47	3.37		
PULL #5	3.39	3.52		
TOTAL				
AVG.				

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.51	4.44		4.38
PULL #2	4.60	4.52		4.35
PULL #3	4.38	4.43		4.56
PULL #4	4.53	4.48		4.36
PULL #5	4.53	4.49		4.54
TOTAL				
AVG.				