

5679 4691

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6794691

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6794691

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		11-11-08	SP
430	ASSEMBLE TO STOCK		11-11-08	SP
440	PROOF		11-11-08	SP
460	CHECK HEADSPACE		11-11-08	SP
470	DIS-ASSEMBLE ACTION		11-11-08	SP
472	SERIALIZE BOLT HANDLE		11-12-08	RT
475	DRILL AND TAP SIGHT HOLES		11-12-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR (A)	11/17/08	(A)
490	MAGNAFLUX BOLT		11/17/08	MR
500	ROLLMARK CALIBER		11/17/08	RT
520	GOFF BLAST BBL / REC		11/17/08	DS
542	APPLY COATINGS (BARREL ACTION)		11-21	—
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-25-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-25-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-25-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-25-08	SP
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	BARBER M24 ED074414	READINGS			DATE	INITIAL		
560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	4.0	4.0	4.0	1-6-09	R.J.		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	8.0	7.0	8.0	1-6-09	L.H.		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	.023	.024	.024	1-6-09	L.H.		
	J) ASSEMBLE STOCK					1-5-09	R.R.		
	K) ASSEMBLE SWIVEL STUDS					1-6-09	L.N.		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S								
	M) IRON SIGHT ALIGNMENT								
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER								
640 & 650	FUNCTION TEST AND TARGET		PASS	FAIL		1-5-09	L.H.		
			PASS	FAIL					
	MALFUNCTION		CORRECTION						
	MALFUNCTION		CORRECTION						
	MALFUNCTION		CORRECTION						
	MALFUNCTION		CORRECTION						
660	INSPECT FOR LIVE AMMO					1-5-09	R.P.		
670	FINAL INSPECTION A) HEADSPACE					1-6-09	L.H.		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	2.55	2.53	2.56	2.53	2.50	1-6-09	T.
	C) FUNCTION					1-6-09	L.H.		
690	PACK					1/15/09	F.M.		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE

11/19/08

TESTER

Tae

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	254	251		268	
PULL #2	250	228		256	
PULL #3	253	228		255	
PULL #4	250	234		258	
PULL #5	251	226		252	
TOTAL	1258	1161		1289	
AVERAGE	251	233		259	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	311	323		
PULL #2	314	310		
PULL #3	314	308		
PULL #4	310	310		
PULL #5	308	309		
TOTAL	2496	1551		
AVERAGE	499	310		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	421	453		474
PULL #2	450	454		463
PULL #3	449	454		465
PULL #4	455	452		463
PULL #5	459	463		464
TOTAL	2232	2276		Tae 3266 2329
AVERAGE	446	455		465