

TRACKING #TLW1447
PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	TOTAL RDS.
				RDS. FIRED	
SW/JS	4/23/04	Head space Min + .003	TLW1447A		
"	"	Head space Belt Type Go won't close			
SW/JS	4/28/04	Proof Ad OK	TLW1447B	1	1
↓	4/29/04	Head space Min + .003	TLW1447C		
"	"	Head space Belt Type Go won't close	"		
SW	4/30/04	Firing Pin Indent .019, .019, .018 Avg. .0186	TLW1447D		
↓	4/30/04	Check Loosening Torque Front Screw 34 in lbs	TLW1447Z		
↓	↓	Check Depth of Front Lockdown Screw hole .0142	↓		
↓	↓	Inspect Thread & measure Length OK / 1.4390	↓		
↓	↓	Engagement .0338, .0336, .0337 Avg. .03370	TLW1447E		
↓	↓	Trigger Pull	TLW1447F		
↓	↓	4.801, 4.728, 4.770, 4.742, 4.815 Avg 4.771	"		
↓	↓	Check number of turns to loosen front screw 1 3/4 Turn	TLW1447Z		
SW	4/28/04	Serv list .0186	TLW1447E		
SW	4/35/04	Torque Front Screw 70 in lbs	TLW1447		
SW	4/39/04	200 Ad Basic Jack Function Test	TLW1447P	200	201
BL	5-6-04	Clean Bore & Bolt			
SW	5/13/04	EJ Functions & Endurance Test 4 - Multi Functions	TLW1447R	500	701
SW	5/18/04	Clean & Inspect Head Space Min + .003	TLW1447S		
SW	5/31/04	Endurance 500 Ad	TLW1447R	500	1201
SW	5/24/04	Clean & Inspect Head Space Min + .003	TLW1447S		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

BARBER - 5.22.06r0004575

Q