GUN # A-32
REM MODEL 710
SERIAL # 71202753
.300 WIN MAG CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

| NAME | DATE | TEST ACTIVITY | COMMENTS | | RDS. FIRED | TOTAL RDS. |
|---|---|---|---|---|---|---|
| B. LEE | 1-25-05 | Initial Headspace | min .003 | TLW1689B | | |
| B. LEE | 1-26-05 | PROOF | ok | TLW1689C | 1 | 1 |
| B. LEE | 1-26-05 | Headspace | min .003 | TLW1689D | | |
| B. LEE | 1-27-05 | Firing Pin Indent | .023 - .021 - .021 Avg .0216 | TLW1689E | | |
| HJC | 1-31-05 | Safe On/Off | Data Sheet | TLW1689I | | |
| HJC | 2-1-05 | Weight | " " | TLW1689A | | |
| HJC | 2-2-05 | Sear Eng-Lift | " " | TLW1689F | | |
| B. LEE | 2-4-05 | Screw Depth | " " | TLW1689A | | |
| B. LEE | 2-4-05 | Trigger Pull | " " | TLW1689H | | |
| B. LEE | 2-7-05 | Firing Pin Head Engagement | " " | TLW1689G | | |
| HJC | 2-7-05 | Screw Detorque Force | " " | TLW1689A | | |
| B. LEE | 2-8-05 | Torque Screws to Spec. | Front 75 in-Lb - middle 30-35 in Lb | | | |
| | | | Rear 15 in Lb | TLW1689 | | |
| PKR | 2/15/05 | POI | Mount Scope, Sight-In, Shoot 1, 5 shot | | | |
| | | | Group | | 8 | 9 |
| JLW | 2-15-05 | JACK FUNCTION | 100 RDS. | TLW1689L | 100 | 109 |
| PKR | 2/18/05 | POI | 1-5 Shot Group | | 5 | 114 |
| JLW | 2-18-05 | JACK FUNCTION | 100 RDS. | TLW1689L | 100 | 214 |
| PKR | 2/18/05 | POI | 1-5 Shot Group | | 5 | 219 |
| B. LEE | 2-21-05 | 0-500 Function Test | 1 stem Low | TLW1689O | 500 | 719 |
| B. LEE | 2-22-05 | Clean/Inspection | ~~[illegible]~~ | TLW1689R | | |
| B. LEE | 2-24-05 | Shoulder Function | | TLW1689M | 10 | 729 |
| B. LEE | 2-24-05 | 501-1000 Function Test | | TLW1689Q | 500 | 1229 |
| B. LEE | 2-25-05 | Clean/Inspection | | TLW1689R | | |

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORM DTDS.XLS

BARBER - 5.22.06T0005010

Confidential - Subject to Protective Order
Williams v. Remington

ET22010