

E67c 15 69

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
rifle.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

Made in Illinois, NY Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.

SERIAL NO. **E6761569**

ORDER NO. **25716**

46

14XV

5716 E6761569

ORDER 25716

MODEL 700™ M24

UPC



ORDER 25716

MODEL 700™ M24

UPC



SERIAL NO.





MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444




ORDER NO. 25716

BARREL LENGTH 24"

CAPACITY 6

E6761569



CONTRACT #

GUN SERIAL # 676 1569

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		9-25-01	AK
600	PROOF		9/25/01	K
607	CHECK HEADSPACE		9-26-01	AK
610	DIS-ASSEMBLE GUN		9-26-01	AK
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT		SEP 29 2001	AC
615	ROLLMARK CALIBER		9/29	AK
617	DRILL AND TAP SIGHT HOLES			
620	APPLY COATINGS (BARREL ACTION)		10/8	AK
	(BOLT)		10/8	AK
625	FINAL ASSEMBLY		11-15-01	AK
	A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-15-01	AK
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-15-01	AK
	D) OIL FIRING PIN ASSEMBLY		10-15-01	AK
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

CONTRACT #

GUN SERIAL # _____

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

OP #	OPERATION NAME		READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>7.0</u> <u>7.0</u> <u>7.0</u>	10-16-01	DA
CONT.	G) SAFETY OFF FORCE	2 LBS MIN	<u>2.5</u> <u>3.0</u> <u>3.0</u>	10-16-01	DA
	H) TRIGGER PULL TEST AND RETAINABILITY				
	I) FIRING PIN INDENT	.020 MIN	<u>.022</u> <u>.023</u> <u>.023</u>	10-16-01	DA
	J) ASSEMBLE STOCK			9-26-01	RZ
	K) ASSEMBLE SWIVEL STUDS			11-6-01	AC
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			11-6-01	AC
	M) IRON SIGHT ALIGNMENT			11-6-01	AC
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			11-6-01	AC
640	GALLERY TEST AND TARGET		PASS FAIL	10-15-01	RW
	A) MALFUNCTIONS		PASS FAIL	10-15-01	RW
	B) PIERCED PRIMERS		PASS FAIL	10-15-01	RW
645	INSPECT FOR LIVE AMMO			10-15-01	RW
655	FINAL INSPECTION A) HEADSPACE			11-01-01	AC
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.50</u> <u>2.45</u> <u>2.43</u> <u>2.44</u> <u>2.45</u>	10-16-01	DA
	C) FUNCTION			11-6-01	AC
660	PACK			12-2-01	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. E6761569DATE 9/27/01TESTER DA

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.35	2.54		2.59	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.21	2.54		2.61	
PULL #3	2.31	2.58		2.42	
PULL #4	2.33	2.52		2.58	
PULL #5	2.35	2.37		2.58	
TOTAL	11.55	12.55		12.78	
AVG.	2.31	2.51		2.55	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.40	3.43		
PULL #2	3.46	3.48		
PULL #3	3.46	3.49		
PULL #4	3.39	3.46		
PULL #5	3.44	3.46		
TOTAL	17.15	17.32		
AVG.	3.43	3.46		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.08	4.05		4.33
PULL #2	4.00	4.12		4.09
PULL #3	4.09	4.00		4.18
PULL #4	4.12	4.11		4.17
PULL #5	4.00	4.10		4.24
TOTAL	20.29	20.38		21.01
AVG.	4.05	4.07		4.20

BARBER - M24 0113493

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # e6761569
15 Oct 2001

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .0108
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.1664
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .16675

THE AMR FOR THIS RIFLE IS: 1.174

CENTROIDAL DISTANCES

Ø TO	1	.205866
1 TO	2	.285414
1 TO	3	.0638122
1 TO	4	.303488
1 TO	5	.449752

2
4 5 <----POA
4

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
 POA TO CENTROID: .206
 MIN RADIUS : .341
 MEAN RADIUS : 1.462
 MAX RADIUS : 2.223
 CENTROID X : -.141
 CENTROID Y : -.150

15 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6761569

CENTERFIRE PATTERN # 1



OF SHOTS= 10

IN CIRCLE

HS= 3.57
 VS= 3.53
 GS= 3.72

1
 2
 5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 2 ☐
 POA TO CENTROID: .085
 MIN RADIUS : .159
 MEAN RADIUS : .929
 MAX RADIUS : 1.935
 CENTROID X : .028
 CENTROID Y : .080

15 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6761569

CENTERFIRE PATTERN # 2



OF SHOTS= 10

IN CIRCLE

HS= 2.12

2

VS= 2.95

6

GS= 3.23

8

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 3 ☐
 POA TO CENTROID: .230
 MIN RADIUS : .397
 MEAN RADIUS : 1.049
 MAX RADIUS : 1.742
 CENTROID X : -.107
 CENTROID Y : -.204

15 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6761569

CENTERFIRE PATTERN # 3



OF SHOTS= 10

IN CIRCLE

HS= 3.29
 VS= 2.32
 GS= 3.41

1
 5
 7

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 4 ☐
 POA TO CENTROID: .435
 MIN RADIUS : .028
 MEAN RADIUS : 1.183
 MAX RADIUS : 2.411
 CENTROID X : -.034
 CENTROID Y : -.434

15 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6761569

CENTERFIRE PATTERN # 4



OF SHOTS= 10

IN CIRCLE

HS= 3.66
 VS= 2.73
 GS= 3.66

2
 3
 5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 5 ☐
 POA TO CENTROID: .331
 MIN RADIUS : .115
 MEAN RADIUS : 1.249
 MAX RADIUS : 2.105
 CENTROID X : .308
 CENTROID Y : -.124

15 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6761569

CENTERFIRE PATTERN # 5



OF SHOTS= 10

IN CIRCLE

HS= 1.79
 VS= 3.91
 GS= 3.93

2
 3
 5