

E6761593


Remington®		VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.	
MODEL 700™ M24 BOLT ACTION CENTERFIRE RIFLE 24" BARREL 7.62 NATO		SERIAL NO. J E6761593	
46		ORDER NO. 25716	
Made in Ilion, NY Reg. U.S. Pat & tm. Off. Marca Registrada Marque Deposee.			
			
5716 E6761593		14XV	

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444



ORDER NO.	25716
BARREL LENGTH	24"
CAPACITY	6

E6761593



ORDER 25716

MODEL 700_{TH} M24

UPC



0 47700 25716 7

ORDER 25716

MODEL 700_{TH} M24

UPC



0 47700 25716 7

SERIAL NO.



E6761593

GUN SERIAL # E676 1593

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		9-25-01	RH
600	PROOF		9/25/01	AC
607	CHECK HEADSPACE	MAGNA - FLUX	9-26-01	RH
610	DIS-ASSEMBLE GUN	INSPECTED	9-26-01	RH
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	SEP 26 2001 OPERATOR DRD		
615	ROLLMARK CALIBER		9/27	RH
617	DRILL AND TAP ^{9/28} SIGHT HOLES BWT	SEND TO NEXT OP	9/27	RH
620	APPLY COATINGS (BARREL ACTION)		10/3	HP
	(BOLT)		10/3	HP
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-9-01	RH
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-9-01	RH
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-9-01	RH
	D) OIL FIRING PIN ASSEMBLY		10-9-01	RH
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

CONTRACT #

GUN SERIAL # _____

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>6.0</u> <u>6.0</u> <u>6.0</u>	10/13/01	DA
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.0</u> <u>3.0</u> <u>3.5</u>	10/13/01	DA
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.021</u> <u>.022</u> <u>.022</u>	10/13/01	DA
	J) ASSEMBLE STOCK			
	K) ASSEMBLE SWIVEL STUDS		11-07-01	K
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640	GALLERY TEST AND TARGET	PASS FAIL	10-12-01	AC
	A) MALFUNCTIONS	PASS FAIL	10-12-01	AC
	B) PIERCED PRIMERS	PASS FAIL	10-12-01	AC
645	INSPECT FOR LIVE AMMO		10-12-01	AC
655	FINAL INSPECTION A) HEADSPACE		11-7-01	K
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.48</u> <u>2.45</u> <u>2.45</u> <u>2.31</u> <u>2.29</u>	10-15-01	DA
	C) FUNCTION		11-7-01	AC
660	PACK		12-3-01	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#
3.00# + .75#
4.00# + 1.00#

SERIAL NO. E6761593DATE 10/1/01TESTER DA

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.55	2.64	2.57	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.44	2.57	2.28	
PULL #3	2.72	2.66	2.66	
PULL #4	2.58	2.69	2.70	
PULL #5	2.64	2.69	2.42	
TOTAL	1293	1325	1263	
AVG.	2.58	2.65	2.52	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.25	3.18	
PULL #2	3.29	3.18	
PULL #3	3.43	3.30	
PULL #4	3.52	3.26	
PULL #5	3.37	3.35	
TOTAL	1686	1627	
AVG.	3.37	3.25	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.34	4.05		4.22
PULL #2	4.35	4.01		4.32
PULL #3	4.21	4.09		4.33
PULL #4	4.38	4.19		4.34
PULL #5	4.20	4.01		4.28
TOTAL	2148	2035		2149
AVG.	4.29	4.07		4.29

BARBER - M24 0113822

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6761593
12 Oct 2001

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.0658$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $.318$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.324736$

THE AMR FOR THIS RIFLE IS: 1.208

CENTROIDAL DISTANCES

0 TO	1	.313423
1 TO	2	.591692
1 TO	3	.740648
1 TO	4	.49261
1 TO	5	.876329

5
4
1
3 2 + <----POA

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .314
 MIN RADIUS : .339
 MEAN RADIUS : 1.087
 MAX RADIUS : 1.676
 CENTROID X : .253
 CENTROID Y : .185

12 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6761593

CENTERFIRE PATTERN # 1



OF SHOTS= 10

IN CIRCLE

HS= 2.35

1

VS= 2.02

4

GS= 3.06

5

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 2 ☐
 POA TO CENTROID: .282
 MIN RADIUS : .155
 MEAN RADIUS : .779
 MAX RADIUS : 1.511
 CENTROID X : -.257
 CENTROID Y : -.115

12 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6761593

CENTERFIRE PATTERN # 2



OF SHOTS= 10

IN CIRCLE

HS= 1.98
 VS= 2.18
 GS= 2.59

2
 8
 9

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 3 ☐

POA TO CENTROID: .459

MIN RADIUS : .249

MEAN RADIUS : 1.206

MAX RADIUS : 1.956


CENTROID X : -.459

CENTROID Y : -.019

12 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EG6761593

CENTERFIRE PATTERN # 3



OF SHOTS= 10

IN CIRCLE

HS= 3.11

1

VS= 2.99

3

GS= 3.64

7

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 4 ☐
 POA TO CENTROID: .499
 MIN RADIUS : .309
 MEAN RADIUS : 1.040
 MAX RADIUS : 1.614
 CENTROID X : -.143
 CENTROID Y : .478

12 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6761593

CENTERFIRE PATTERN # 4



OF SHOTS= 10

IN CIRCLE

HS= 2.78
 VS= 2.06
 GS= 3.01

2
 5
 9

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 5
 POA TO CENTROID: 1.097
 MIN RADIUS : 1.322
 MEAN RADIUS : 1.929
 MAX RADIUS : 2.743
 CENTROID X : .277
 CENTROID Y : 1.061

12 Oct 2001

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6761593

CENTERFIRE PATTERN # 5



OF SHOTS= 10

IN CIRCLE

HS= 3.48

0

VS= 4.29

0

GS= 5.38

3