

UPC



E6374630

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

* INCLUDES 1 IN CHARGE

Do Not Use

Remington®		VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.
MODEL 700™ M24 BOLT ACTION CENTERFIRE RIFLE 24" BARREL 7.62 NATO 6*		SERIAL NO. E6374630
Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.		46 ORDER NO. 25705
 5705 E6374630		19RR

Do Not Use

ORDER 25705

MODEL 700T^m M24

UPC



ORDER 25705

MODEL 700T^m M24

UPC



SERIAL NO.



E6374630

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINS:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

proof of purchase



E66374630

gunney registration sticker



E66374630

BARBER - M24 0119134

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6374630
8 Nov 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.0296667
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.0753333
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .0809643

THE AMR FOR THIS RIFLE IS: .8103

CENTROIDAL DISTANCES

0 TO 1	.266595
1 TO 2	.32256
1 TO 3	.268412

$\begin{matrix} 2 \\ 3 \end{matrix}$ <----POA
1

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.


PATTERN #: ☐ 1 ☐

POA TO CENTROID: .267
 MIN RADIUS : .160
 MEAN RADIUS : .731
 MAX RADIUS : 1.295
 CENTROID X : -.168
 CENTROID Y : -.207

8 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E637463D

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 2.06

2

VS= 1.12

4

GS= 2.07

5

PATTERN #: ☐ 2 ☐

POA TO CENTROID: .063

MIN RADIUS : .492

MEAN RADIUS : 1.151

MAX RADIUS : 1.906


CENTROID X : .010

CENTROID Y : .062

8 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E637463D

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.43

1

VS= 3.36

3

GS= 3.58

3

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 3 ☐
 POA TO CENTROID: .106
 MIN RADIUS : .266
 MEAN RADIUS : .549
 MAX RADIUS : .809
 CENTROID X : .069
 CENTROID Y : -.081

8 Nov 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E637463D

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.16
 VS= 1.15
 GS= 1.40

2
 5
 5

BARBER - M24 0119138

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6374630
31 Oct 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.160667
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .045
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .16685

THE AMR FOR THIS RIFLE IS: 1.336

CENTROIDAL DISTANCES

0 TO 1 .243288
1 TO 2 .578705
1 TO 3 .0930591


31
+ <----POA
2

PATTERN #: ☐ 1 ☐
 POA TO CENTROID: .243
 MIN RADIUS : .482
 MEAN RADIUS : 1.201
 MAX RADIUS : 2.109
 CENTROID X : -.070
 CENTROID Y : .233

31 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6374630

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 3.21

1

VS= 1.81

1

GS= 3.31

4


PATTERN #: 2

POA TO CENTROID: .403
 MIN RADIUS : .064
 MEAN RADIUS : 1.830
 MAX RADIUS : 2.794
 CENTROID X : -.250
 CENTROID Y : -.317

31 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6374630

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 3.45
 VS= 3.92
 GS= 5.14

1
 1
 1


PATTERN #: ☐ 3 ☐

POA TO CENTROID: .273
 MIN RADIUS : .240
 MEAN RADIUS : .976
 MAX RADIUS : 1.887
 CENTROID X : -.162
 CENTROID Y : .219

31 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E637463B

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 2.08

2

VS= 2.96

3

GS= 3.63

3

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E 6374630

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	BARBER - M24 0119143 F) SAFETY ON FORCE	<u>5</u> <u>5</u> <u>5</u>	11-3-97	CR
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>3</u>	11-3-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.022</u> <u>.022</u> <u>.022</u>	11-3-97	CR
	J) ASSEMBLE STOCK		10-30-97	RW
	K) ASSEMBLE SWIVEL STUDS		11-1-97	CH
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		11-30-97	RW
	M) IRON SIGHT ALIGNMENT		10-30-97	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10-30-97	RW
640	GALLERY TEST AND TARGET	L 64 R 86	10/31/97 11-3-97	PB DB
	A) MALFUNCTIONS		10/31/97 11-3-97	PB DB
	B) PIERCED PRIMERS		10/31/97 11-8-97	PB DB
645	INSPECT FOR LIVE AMMO		10/31/97 11-8-97	DB DB T M
655	FINAL INSPECTION A) HEADSPACE		11-11-97	CK
	B) TRIGGER PULL	<u>2.42</u> <u>2.44</u> <u>2.58</u> <u>2.36</u> <u>2.35</u>	11/10/97	TRP
	C) FUNCTION		11-11-97	CK
660	PACK			

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#

3.00# + .75#

4.00# + 1.00#

SERIAL NO. E6374630DATE 10-29-97TESTER TM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.37	2.35	2.36		MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.35	2.30	2.35		
PULL #3	2.42	2.39	2.29		
PULL #4	2.35	2.32	2.34		
PULL #5	2.42	2.38	2.39		
TOTAL	11.91	11.74	11.73		
AVG.	2.38	2.34	2.34		

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.04	2.98		
PULL #2	2.97	2.92		
PULL #3	2.99	2.93		
PULL #4	2.95	2.99		
PULL #5	2.95	2.95		
TOTAL	14.90	14.77		
AVG.	2.98	2.95		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	3.99	4.07		4.21
PULL #2	4.02	3.99		4.17
PULL #3	3.95	3.89		4.18
PULL #4	4.10	4.01		4.11
PULL #5	3.99	4.01		4.08
TOTAL	20.05	19.97		20.75
AVG.	4.01	3.99		4.15