

UPC



E6349850

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

BARBER - M24 0122888

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6349850
28 Jul 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.0796667$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $.00166667$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.0796841$

THE AMR FOR THIS RIFLE IS: 1.247

CENTROIDAL DISTANCES

0 TO 1	.236212
1 TO 2	.551567
1 TO 3	.662109


2 1
 + <----POA
 3

PATTERN #: 1
 POA TO CENTROID: .236
 MIN RADIUS : .370
 MEAN RADIUS : .972
 MAX RADIUS : 1.699
 CENTROID X : .100
 CENTROID Y : .214

28 Jul 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349858

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 2.03

1

VS= 2.23

3

GS= 3.01

4

BARBER - M24 0122890


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
POA TO CENTROID: .510
MIN RADIUS : 1.152
MEAN RADIUS : 1.515
MAX RADIUS : 2.627
CENTROID X : -.451
CENTROID Y : .239

28 Jul 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EG349858

CENTERFIRE PATTERN # 2

OF SHOTS= 5

IN CIRCLE

HS= 4.02

0

VS= 2.01

0

GS= 4.02


4

PATTERN #: 3
 POA TO CENTROID: .462
 MIN RADIUS : .431
 MEAN RADIUS : 1.255
 MAX RADIUS : 1.921
 CENTROID X : .112
 CENTROID Y : -.448

28 Jul 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349858

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 3.53

1

VS= 1.29

1

GS= 3.56

3

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. E6349850DATE 7-10-97TESTER G.W.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.52	2.57	2.56	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.66	2.63	2.58	
PULL #3	2.54	2.42	2.55	
PULL #4	2.55	2.52	2.57	
PULL #5	2.60	2.49	2.57	
TOTAL	12.83	12.63	12.77	
AVG.	2.566	2.526	2.554	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	2.92	3.19	
PULL #2	3.01	3.21	
PULL #3	3.12	3.22	
PULL #4	3.06	3.20	
PULL #5	3.23	3.05	
TOTAL	15.34	15.87	
AVG.	3.068	3.174	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.12	4.22		4.13
PULL #2	4.01	4.20		4.05
PULL #3	4.13	4.24		3.97
PULL #4	3.99	4.19		4.10
PULL #5	3.87	4.21		3.93
TOTAL	20.12	21.06		20.18
AVG.	4.024	4.212		4.036

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E 6349850


OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>4</u> <u>4</u> <u>4</u>	2-28-97	CK
CONT.	G) SAFETY OFF FORCE	<u>2</u> <u>3</u> <u>3</u>	2-28-97	CK
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.021</u> <u>.021</u> <u>.021</u>	2-28-97	CK
	J) ASSEMBLE STOCK		7-17-97	CR
	K) ASSEMBLE SWIVEL STUDS		8/13/97	RP
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		7-17-97	CR
	M) IRON SIGHT ALIGNMENT		7-17-97	CR
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		7-17-97	CR
640	GALLERY TEST AND TARGET	R 82 L 68	7/28/97	KT
	A) MALFUNCTIONS		7/28/97	KT
	B) PIERCED PRIMERS		7/28/97	KT
645	INSPECT FOR LIVE AMMO		7/28/97	GW
655	FINAL INSPECTION A) HEADSPACE		8/13/97	RP
	B) TRIGGER PULL	<u>2.44</u> <u>2.45</u> <u>2.75</u> <u>2.56</u> <u>2.33</u>	6-7-97	CK
	C) FUNCTION		8/13/97	RP
660	PACK			

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

- GREEN ENVELOPE CONTAINING:
- INSTRUCTION BOOK
 - PRODUCT OWNER'S CARD
 - MUSEUM/COUNTRY STORE FLIER
 - REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Do Not Use

VERY IMPORTANT: Instruction Book enclosed to assure safe use of this firearm.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

SERIAL NO. E6349850

46 ORDER NO. 25705

26WR

5705 E6349850

REG. U.S. Pat. & Tm. Off. Marca Registrada. Marque Déposée.

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



E6349850