

CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean & Inspect Checklist

Model: 710 Extruded Receiver "Std. Caliber"

Project: 241314

TLW #: TLW1689

Date: 2 / 17 / 05

Gun Test # A-2

S/N 71202775

Round Level: 701

Inspector: B. LEE

☒ Measure Headspace min. .004

☒ Check Takedown Screw Torque @ Disassembly: Frt 45, Center 30, Rear 10

☒ Sear Engagement: 1<sup>st</sup> .0235 2<sup>nd</sup> .0250 3<sup>rd</sup> .0253 Ave. .0246 spec- .020" to .025"

☐ Reset Sear Engagement if Required: 1<sup>st</sup>      2<sup>nd</sup>      3<sup>rd</sup>      Ave.     

☒ Trigger Pull: 1<sup>st</sup> 6.186 2<sup>nd</sup> 5.980 3<sup>rd</sup> 5.683 Ave. 5.950 spec- 4 lb. to 5.5 lb.

☒ Reset Trigger Pull if Required: 1<sup>st</sup> 5.278 2<sup>nd</sup> 5.091 3<sup>rd</sup> 5.059 Ave. 5.143

☒ Inspect Firecontrol Insert for any signs of cracking or other failure. OK

☐ Other items of note:       
      
    

☒ Torque Takedown Screws @ Reassembly: SPEC- Frt- 50 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.

TLW1216

Remington Confidential

ET22201