

66764910

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



3J FORM


ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

G6764910

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6764910

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		6-24-08	RP
430	ASSEMBLE TO STOCK		6-24-08	JP
440	PROOF		6-24-08	SD
460	CHECK HEADSPACE		6-24-08	SD
470	DIS-ASSEMBLE ACTION		6-24-08	RP
472	SERIALIZE BOLT HANDLE		7-10-08	JP
475	DRILL AND TAP SIGHT HOLES		JUL 15, 2008 6-24-08	SD
480	MAGNAFLUX BBL ACTION		7-11-08	(K)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7-11-08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		7-21	C
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		7-22-08	JP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		7-22-08	JP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		7-22-08	JP
	D) OIL FIRING PIN ASSEMBLY		7-24-08	
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATOR NAME	0128694	READINGS			DATE	INITIAL		
560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>5.5</u>	<u>5.5</u>	<u>5.5</u>	7-30	TL		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	<u>7.5</u>	<u>7.5</u>	<u>7</u>	7-30	TL		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	<u>.021</u>	<u>.022</u>	<u>.022</u>	7-30	TL		
	J) ASSEMBLE STOCK					7-24-08	RSW		
	K) ASSEMBLE SWIVEL STUDS					8-28-08	RSW		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S								
	M) IRON SIGHT ALIGNMENT								
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER								
640 & 650	FUNCTION TEST AND TARGET		<u>PASS</u>	FAIL		7-26-08	TRW		
			<u>PASS</u>	FAIL					
	MALFUNCTION	CORRECTION	N/A						
	MALFUNCTION	CORRECTION							
	MALFUNCTION	CORRECTION							
	MALFUNCTION	CORRECTION							
660	INSPECT FOR LIVE AMMO					7-26-08	TL		
670	FINAL INSPECTION A) HEADSPACE					8-28-08	RSW		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.95</u>	<u>2.95</u>	<u>2.96</u>	<u>2.96</u>	<u>2.84</u>	7-30-08	RSW
	C) FUNCTION					8-28-08	RSW		
690	PACK					8-29-08	TL		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE

7-21-08

TESTER

S. Day

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.73	2.59		2.56	
PULL #2	2.63	2.60		2.46	
PULL #3	2.71	2.46		2.53	
PULL #4	2.70	2.43		2.42	
PULL #5	2.72	2.46		2.36	
TOTAL	1349	1254		1233	
AVERAGE	2.69	2.50		2.46	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.31	3.40		
PULL #2	3.33	3.46		
PULL #3	3.50	3.30		
PULL #4	3.57	3.31		
PULL #5	3.47	3.35		
TOTAL	1718	1682		
AVERAGE	3.43	3.36		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.10	4.09		4.04
PULL #2	4.04	4.08		4.01
PULL #3	4.02	3.98		4.11
PULL #4	4.02	4.01		4.12
PULL #5	4.02	3.98		4.19
TOTAL	2020	2014		2047
AVERAGE	4.04	4.02		4.09