

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 10 17 103Inspector: B LeeRound Level: 3261

- ☒ Measure Headspace Min 7.006
- ☒ Sear Engagement: 1st .0249 2nd .0246 3rd .0250 Ave. .0247 spec. .020" to .025" 83
- ☐ Reset Sear Engagement if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____
- ☒ Trigger Pull: 1st 4.515 2nd 4.611 3rd 4.455 Ave. 4.527 spec. 4 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear wear on bolt stop
- ☒ Inspect stock for any signs of cracking or other failure. Cracks in stock
- ☒ Other items of note: Top of magazine box has some protrusion wear in magazine latch area / Replace magazine box.
- Photos taken of chamber w/ scope 3 rear / 3 front

TLW1216

Remington Confidential

ET22477