

MURDER 721-772 - MURDER

Make	Model	Price	Dealer's Discount	Jobber's Cost to Remanufacturer	Remarks
Packmeyer	"Lo-Swing"	\$ 20.00	33-1/3%	50%	50 & 10%
	(Quotes per their letter 4/23/48)				Means of Attachment Four (4) screws left side Receiver. (Drill jig available - \$5.00 deposit.)
					Inlet Stock Yes
					Reman. All scopes not larger than 1" dia. Reman. Being shipped.
Stith	"Masters"	20.00	33-1/3%	433-1/3%	433-1/3%
	(*) Present terms - subject to change.				Means of Attachment Front - present holes in top of Receiver. - Rear side plate furnished to suit present holes at left rear of Receiver - Rear Mount Plate for top Receiver on request.
	(All quotes in letter W.J. Stith to S.M. Alvis 4-21-48)				Inlet Stock Yes
					Reman. Practically all American Hunting & small game scopes - Specify head size - 3/4", 7/8", and 1"
					Reman. Yes on W/721 No. 23601.
"C.E.D. Style"	(Install-It-Yourself)	15.00	33-1/3%	50%	50%
					Means of Attachment Rear slight dovetail slot and present tapped holes - Rear - Left side Receiver.
					Inlet Stock Yes (?)
					Reman. Weaver E-2.5; S-4; E-4; E-6 J-2.5 or J30-440
	" (For Weaver J-2.5) 12.00	33-1/3%	50%	50%	Alaskan - Reman
					Means of Attachment Same as above
					Inlet Stock Yes (?)
					Reman. Shipped
"C.E.D. Windage Type"	15.00	33-1/3%	50%	50%	50%
					Means of Attachment Same as above.
					Inlet Stock Yes
					Reman. Bear-Club & Weaver S-4
					Reman. Shipped
"Install-It-Yourself"	15.00	33-1/3%	50%	50%	50%
					Means of Attachment Same as above.
					Inlet Stock Yes (?)
					Reman. Alaskan - Temp & Weaver E-2.5; S-4
Lokley	"Boop-On"	14.95	(Will advise)		
					Means of Attachment Present top holes - Top Front Receiver; two holes - top Rear Receiver.
					Inlet Stock No
					Reman. 7/8" & 1" Dia. Rings
					Reman. Yes

MODEL 721-722 - MOUNTS
Sheet 2

Redfield-Jr.	(3/4" Rings) (22mm. Rings) (1" Rings) (26 mm. Rings)	10.75) 12.75) 14.75) 17.75)	33-1/3%	50%	60%	Means of Attachment: Present two holes - Top Front of Receiver; 1 add. hole top Rear Bridge of Receiver. Inlet Stock: No Screws: To Bolt Ring Sizes Screws: Yes
Beaver "Type 'C' "		5.75	3.50-4.20	2.90	2.90	Means of Attachment: Present holes in Receiver Front & Rear Inlet Stock: Yes - for Rear Screws: 3/4" Screws - Any of Weaver type Series. Screws: On Head Means of Attachment: Uses C-14 Front Ring Q-10 Rear Mount Q-14 Front Ring Q-10 Rear Mount
Griffin & Howe		6.25	3.60-4.60	3.20	3.20	Inlet Stock: Yes - Rear Screws: 1" Screws; Any of Weaver type Series. Means of Attachment: Flange Pinned (aligned) to Left Side of Receiver. Inlet Stock: Yes Screws: Aluminum - Taper, etc. Requires Special Tooling to fit. Remington not equipped.
Williams "QC"		17.50	33-1/3% (1 to 12) 40% (more than 12)	50% & 25 Not 10	50% & 25 Not 10	Means of Attachment: Uses the present two holes in Front of Receiver; Requires drill & tap one hole in Rear Top of Rec. Bridge. Inlet Stock: No Screws: Tube Dia. 3/4", 7/8" & 1" Rings. Screws: Leopold, Lyman, etc. Rever
"QD"		12.50	(For their letter to S.M. Alvin 4-13-48)			