

REMINGTON ARMS COMPANY, INC.
INTER-DEPARTMENTAL CORRESPONDENCE

Remington
10-10

RECEIVED
JAN 11 1963
OFFICE - F.O.B. - R.S.
10-10-63

To: Wayne Leek
From: K. D. Oslund

XP100 Test rig

Dear Wayne:

Before making any suggestions on the XP100 I think it would be a nice thing to insert a piece of cardboard between the carrying case & shipping box. On opening my box & using a knife to cut the sealing strip I cut slightly into the case. There is no doubt that dealers will open the box the same way - a piece of cardboard between the carrying case & the shipping box will eliminate this.

We've had some terrible weather receiving the gun and ammo.

I'd suggest that the dealer be around the front of the box to open it.

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE



is slick & to me makes it hard to hold.
 I improved my grips as soon as I
 wound the grip with electrician's friction
 tape.

I don't go along with the way the sights
 are adjusted - Also a feel of "would be better."

The arm felt muzzle light and hard to
 hold without a mottle - I taped a piece of electrical
 lead wire to the fore end of the stock - it helped
 me a great deal -

Ejection, extraction & feeding OK.

Should add that in taping the electrical lead
 wire to the fore end it was of greater length than
 standard bullet lengths would be.

Thump at base with contact of heel of hand seems too
 rough.

Would suggest the trigger finger be held in
 by pressure to keep it in line with the slot of the trigger guard.
 It does not line up easily & sometimes force is used
 to keep it from the trigger - consideration could be
 given to this.

REMINGTON ARMS COMPANY, INC.

INTERDEPARTMENTAL CORRESPONDENCE



Triggers pull excellent.

My folder on the XP-100 shows the
fold release in plain sight. which it is not.

Safety OK.

Regards,
Ray Colman

P.S.
In the letter sent me. as soon as I
completed test I was to return arm to you.
It is going out by express to you to-morrow.

As a suggestion Wayne may not give us a Target
22 into pistol using H&S?!!