

TLW _____

Project No. 241095**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST**

Gun
~~Firearm~~ No. B
 Dry Cycles/Rounds
 Model No. 710
 Trigger Pull at Start
 Average Trigger Pu
 Trigger Pull at End
 Average Trigger Pu

Jar-Off Test w/2-3°
 connector angle.
 12/4/00.

12/4/00
 Start _____
 End _____
 (6) _____
 : _____
 (6) _____
 : _____

New 245

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: For Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>		<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass ☒	Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass ☒	Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass ☒	Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass ☒	Fail _____	_____

ET27939