

Orig. 7-1-65
REVISED DEC 14 1965

REMINGTON STANDARDS ARMS

SHEET 1

MODEL 600 MAGNUM		350 Rem. Mag.	6.5MM Rem. Mag.
ACCURACY			
Range	100 yds.		
Point of Aim	6 o'clock on target		
Center of Impact	Not more than 2 inches below or 4 inches above		3 inches either side of point of aim.
Group Size (E.S.)	5 shots - 1/2"		5 shots - 1/2"
Ammunition	200 gr. P&B		?
ACTION			
Bolt action, hand operated, Removable bolt, Solid frame with takedown stock. Bolt goes as handle is raised. Rifle cocks as bolt handle is lowered to lock action closed. Extracts and ejects as bolt is "opened". Direct action trigger. 2 stop safety - Forward to FIRE position - rearward to ON SAFE stop position.			
Action must feed, fire, extract and eject (include extraction and ejection without firing) satisfactorily with all varieties of ammunition listed as standard (for tabulated calibers in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers Institute (SAAMI)).			
ANNOUNCEMENT			
Jan.		1965	1966
June			
*Ref: Genl. Mgt. approved release to Production of 6.5MM Rem. Mag. June 9, 1965			
48 Por. W. E. Leak 12-14-65 (Verbal)			

BARBER - PRESALE R 0103070

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

BARBER - PRESALE R 0103070
R2504058