

GUN# M-L
SERIAL # 71147414
CAL- 30.06 SPRG.

REMINGTON M/710
NON-ISS BOLT PLUG
DAILY TEST DATA SHEET

TRACKING # TLW1349
PROJECT # MAYFIELD SUPPORT

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
J. Sims	12/5/03	INITIAL HEADSPACE	.003		
J. Sims	12/5/03	PROOF TEST	OK	1	1
J. Sims	12/5/03	HEADSPACE AFTER PROOF	.003		
J. Sims	12/5/03	FIRING PIN INDENT	.020, .021, .022		
		TRIGGER/SEAR ENGAGEMENT	eng. .0308, .0303, .0308 Avg. .0306 / Sear lift .0152 / reset eng. .021, .0197, .0201 Avg. .0202		
BL/JS	12-8-03	TRIGGER PULL	4.329-4.379-4.198 Avg. 4.368 S.O.S. 4.081		
BL/JS	12-8-03	JACK FUNCTION TEST	No Jack Function	40	41
BL/JS	12-8-03	SETUP FOR SAAMI TESTING	Top of scope mount 25 in lb / scope to in lb / take down Screws top in lb - lower 25 in lb		
BL/JS	12-8-03	SAAMI ROTATION W/SCOPE	Pass Rotation		
BL/JS	12-9-03	Re-measure	engage - trigger pull		
BL/JS	12-9-03	SAAMI JARR-OFF W/SCOPE	pass jar-off		
BL/JS	12-9-03	Re-measure	engagement - trigger pull		
BL/JS	12-10-03	SAAMI DROP W/SCOPE	pass drop w/ scope		
BL/JS	12-10-03	Remeasure	engagement - trigger pull		
BL/JS	12-10-03	RESET TO STD. SPECS.	reset eng. .0226, .0215, .0217 Avg. .0219 Trigger pull 4.365-4.367-4.294-4.575-4.280 Avg 4.044		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

BARBER - 5.22.06r0007314

ET33802

Confidential - Subject to Protective Order
BARBER - 5.22.06r0007314
Williams V. Remington