

TLW 1349Project No. 24131430.06**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST****JAR-OFF TEST**

Firecontrol No. A2 Firecontrol Type: Standard Date: 12-9-03
 Dry Cycles/Rounds Completed: _____ Stock Type SVN
 Engagement at Start (1) .020 (2) .0206 (3) .0202 Average .0202
 Engagement at End (1) .0197 (2) .020 (3) .0201 Average .0199
 Model No. M/710 Serial No. 71147414
 Trigger Pull at Start of Test (1) 4.260 (2) 3.933 (3) 4.275 (4) 3.683 (5) 3.929
 Average Trigger Pull at Start of Test: 4.016 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.222 (2) 4.042 (3) 4.265 (4) 4.196 (5) 4.050
 Average Trigger Pull at End of Test: 4.156 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: RL/JS

Additional Notes and Comments

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Jar-Off Test:

Jar-Off Test: 12-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm ready to fire, Safe in "Fire" position, Fresh Primed Case in
 Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, fire Primed Case to verify firearm will still function.

12 inch drop (safety in "Fire" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The ISS will be set in the unlocked
 position for all six orientations of the Jar-Off Test

<u>Orientation</u>	<u>ISS Unlocked</u>		<u>Comments</u>
Barrel Vertical, Muzzle Up:	Pass <input checked="" type="checkbox"/>	Fail _____	_____
Barrel Vertical, Muzzle Down:	Pass <input checked="" type="checkbox"/>	Fail _____	_____
Barrel Horizontal, Left side of Stock Up:	Pass <input checked="" type="checkbox"/>	Fail _____	_____
Barrel Horizontal, Right side of Stock Up:	Pass <input checked="" type="checkbox"/>	Fail _____	_____
Barrel Horizontal, Bottom of Stock Up:	Pass <input checked="" type="checkbox"/>	Fail _____	_____
Barrel Horizontal, Bottom of Stock Down:	Pass <input checked="" type="checkbox"/>	Fail _____	_____

Notes: (continue on back of sheet if necessary)

Tester's Initials RL/JS

Page 1 of 3

Z101DROPTTEST_REV5.DOC

ET33803

TLW 1349Project No. 241314**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST****ROTATION TEST**

Firecontrol No. A-2 Firecontrol Type: standard Date: 12/8/03
 Dry Cycles/Rounds Completed: _____ Stock Type syn
 Engagement at Start (1) .021 (2) .0207 (3) .0201 Average .0206
 Engagement at End (1) .020 (2) .0206 (3) .0202 Average .0202
 Model No. M/710 Serial No. 71147414
 Trigger Pull at Start of Test (1) 4.205 (2) 4.166 (3) 4.045 (4) 3.955 (5) 4.081
 Average Trigger Pull at Start of Test: 4.090 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.260 (2) 3.933 (3) 4.275 (4) 3.683 (5) 3.929
 Average Trigger Pull at End of Test: 4.016 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: BL/JS

Additional Notes and Comments

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Rotation Test:

Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with the
 ISS system in the unlocked position for both orientations of the Rotation Test.

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail <input type="checkbox"/>	

Notes: (continue on back of sheet if necessary)

Tester's Initials BL, JS

TLW 1849Project No. 241314**S.A.A.M.I. JAR-OFF, DROP & ROTATION TEST****DROP TEST**

Firecontrol No. A-2 Firecontrol Type: Standard Date: 12-9-03
 Dry Cycles/Rounds Completed: _____ Stock Type SYN Engagement at Start _____
 Engagement at Start (1) .0204 (2) .0206 (3) .0206 Average .0205
 Engagement at End (1) .0199 (2) .0204 (3) .0208 Average .0203
 Model No. m/710 Serial No. 71147414 Engagement at End _____
 Trigger Pull at Start of Test (1) 4.238 (2) 4.126 (3) 3.874 (4) 3.958 (5) 3.993
 Average Trigger Pull at Start of Test: 4.038 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 4.404 (2) 4.438 (3) 4.373 (4) 4.364 (5) 4.264
 Average Trigger Pull at End of Test: 4.369 Std. Dev. of Trigger Pull at End of Test: _____
 Tester Initials: BL / JS

Additional Notes and Comments

Trigger Pull set at 4.444

83

For additional details on the proper procedures to be used for this Test Procedure refer to:

ANSI / SAAMI Z299.5-1990

SAAMI Specifications for Standard Drop Test:**Drop Test:**

48-inch drop - onto 1" thick 85 Durometer (Shore A) Rubber Matt
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop Fire Primed Case to verify firearm will still function.

48 inch drop (safety in "Safe" position) - one drop per orientation.

Note: for Firearms with the ISS system installed - The Firearms will be set with theISS system in the unlocked position for all six orientations of the Drop Test

Orientation	ISS Unlocked	Comments
Barrel Vertical, Muzzle Up:	Pass <u>/</u> Fail _____	
Barrel Vertical, Muzzle Down:	Pass <u>/</u> Fail _____	
Barrel Horizontal, Left side of Stock Up:	Pass <u>/</u> Fail _____	<u>Bolt came open</u>
Barrel Horizontal, Right side of Stock Up:	Pass <u>/</u> Fail _____	
Barrel Horizontal, Bottom of Stock Up:	Pass <u>/</u> Fail _____	
Barrel Horizontal, Bottom of Stock Down:	Pass <u>/</u> Fail _____	<u>Bent Scope</u>

Notes: (continue on back of sheet if necessary)

Tester's Initials BL / JSPage 3 of 3
Z101\DROPTEST_REV5.DOC

ET33805