

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 RDLSerial No. 106752973Headspace as Received: _____Safe - "ON" - I. 7.50"OFF" - I. 8.00Proof: _____(6.3)
2. 6.00
3. 5.502. 7.50
3. 7.00Headspace after Proof: MIN + .004Firing Pin Indent(in.)(10255)
1. .025
2. .025
3. .026Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)(4.5)
1. 4.50
2. 4.50
3. 4.50Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

S
1-12-82