

Start of test

Gun 2

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A6744869Headspace as Received: M +.003Safe - "ON" - I. 6.75 "OFF" - I. 5.50Proof: OK(6.5) 2. 6.50 (5.3) 2. 5.25
3. 6.25 3. 5.25

Headspace after Proof: _____

Firing Pin Indent(in.)

Sear lift .0135
Sear Engagement .026(1023) I. .10235
2. .1023
3. .1023Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)(13) I. 4.75
2. 4.25
3. 4.00Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

I-12-82