

After 2,000 Rounds

5-12-82

Gun-2

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6 MMSerial No. A 6744869Headspace as Received: Mt. 0.004Safe - "ON" - I. 5.5"OFF" - I. 5.0Proof: OK

1. 5.7
2. 6.0
3. 5.5

1. 4.5
2. 5.0
3. 4.5

Headspace after Proof: _____

Firing Pin Indent(in.)Bolt Open Force(lbs.)1. .023

Sear lift .014

Cocked: I. _____

Dry Fired: I. _____

2. .023

Sear Engagement .029

2. _____

2. _____

3. .023

3. _____

3. _____

Trigger Pull(lbs.)Bolt Release Force(lbs.)1. 4.5

I. _____

2. 4.0

2. _____

3. 4.0

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

EJS
1-12-82