

After 1,000 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A 6745544Headspace as Received: M + .002Safe - "ON" - I. 7.5"OFF" - I. 5.0Proof: OK6.8 2. 7.03. 6.05.2 2. 5.03. 5.5

Headspace after Proof: \_\_\_\_\_

Firing Pin Indent(in.)0.22 1. .0222. .0223. .022Bolt Open Force(lbs.)

Cocked: I. \_\_\_\_\_

Dry Fired: I. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull(lbs.)4.0 1. 4.02. 4.03. 4.0Bolt Release Force(lbs.)

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: \_\_\_\_\_

Gun Weight: \_\_\_\_\_

Center of Gravity: \_\_\_\_\_

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: OK

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

• Tester and Date: \_\_\_\_\_

CJS  
I-12-82