

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEET

Model

700

Serial No.

N6745544

(4)

Headstace as Received: _____Safe - "ON" - I. 8.50"OFF" - I. 4.50Proof: _____(8.8) 2. 10.50
3. 7.50(43) 2. 4.00
3. 4.50Headstace after Proof: MIN + .003Firing Pin Indent(in.)I. .0222. .0223. .022Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)I. 4.502. 4.003. 4.50Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: O.K.

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

73

I-12-82