

Start of Test

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 16mmSerial No. 1-6752973Headstace as Received: _____✓ Safe - "ON" - I. 8.0"OFF" - I. 7.0Proof: _____Headspace after Proof: MIN 4.0042. 7.5
3. 6.02. 7.5
3. 6.0✓ Firing Pin Indent (in.)1. 1.0252. 1.0253. 1.025LeadLeft , 010
Right , 013Bolt Open Force (lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

✓ Trigger Pull (lbs.)1. 5.752. 5.753. 5.755.75Bolt Release Force (lbs.)

I. _____

2. _____

3. _____

Gun Length: _____Gun Weight: _____Center of Gravity: _____Bore: _____Choke: _____Orifice Size: _____Bolt Closing Velocity: _____Magazine Spring Force: _____Disconnecter Check: _____Primer Marking: _____Safety Check: _____Firing Pin Protrusion: _____Pattern Test (Avg. of 5)Group Size: _____Horz.: _____Vert.: _____Accuracy (Avg. of 5)Group Size: _____Horz.: _____Vert.: _____ P.O.I.: _____• Tester and Date: _____CJS
I-12-82