

After 1,000 Rounds

①

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A6752973Headspace as Received: _____Safe - "ON" - I. 5.50"OFF" - I. 8.50Proof: _____2. 5.502. 8.50Headspace after Proof: MIN. + .0043. 5.503. 8.50Firing Pin Indent(in.)I. .02552. .0253. .025Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)I. 7.002. 6.503. 6.50Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____Primer Marking: _____Gun Weight: _____Safety Check: _____Center of Gravity: _____Firing Pin Protrusion: _____Bore: _____Pattern Test (Avg. of 5)Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____Accuracy (Avg. of 5)Disconnector Check: _____

Group Size: _____

Horz.: _____

Vert.: _____

P.O.I.: _____

CJS

• Tester and Date: _____

I-12-82

After 2,000 Rounds
SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

(1)

TEST PROCEDURE SHEETModel 700 6MMSerial No. A6752973

Headspace as Received: _____

Safe - "ON" - 1. 9.0"OFF" - 1. 6.5

Proof: _____

2. 7.06.0 2. 5.0Headspace after Proof: M + .0043. 7.03. 6.5Firing Pin Indent(in.)1. .0252. .0253. .025

(.025)

*leave
lift .010
eng. .016*

Trigger Pull(lbs.)1. 5.752. 5.753. 6.5

(6.0)

Bolt Open Force(lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82

After 2,500 Rounds

6-11-82

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A6752973Headspace as Received: _____Safe - "ON" - I. 6.5"OFF" - I. 5.0Proof: _____(w) 2. 6.0
3. 6.0(5.1) 2. 5.5
3. 5.0Headspace after Proof: M + .004Firing Pin Indent(in.)I. .0222. .0223. .022Seare
lift .011
eng. .016Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)I. 6.502. 6.253. 6.25

(6.3)

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS

I-12-82