

J 1915 of 1251

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6mmSerial No. A 6744869Headspace as Received: \_\_\_\_\_Safe - "ON" - I. 8.5"OFF" - I. 5.00Proof: \_\_\_\_\_2. 8.52. 5.253. 8.53. 5.00Headspace after Proof: MIN. 7.004Firing Pin Indent(in.)1. .0232. .02353. .023Lead  
lift .012  
long .013Bolt Open Force(lbs.)

Cocked: I. \_\_\_\_\_

Dry Fired: I. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull(lbs.)1. 5.252. 4.753. 5.25

(508)

Bolt Release Force(lbs.)

I. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: \_\_\_\_\_

Gun Weight: \_\_\_\_\_

Center of Gravity: \_\_\_\_\_

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

• Tester and Date: \_\_\_\_\_

CJS  
I-12-82

After 1,000 Rounds

(2)

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A6744869Headstace as Received: \_\_\_\_\_Safe - "ON" - I. 5.50"OFF" - I. 6.50Proof: \_\_\_\_\_5.00 2. 7.50  
3. 5.006.6 2. 6.50  
3. 7.00Headstace after Proof: MIN+.004Firing Pin Indent(in.)I. .023.023 2. .0243. .024Seal left .013  
Eng 1 .0115Bolt Open Force(lbs.)

Cocked: I. \_\_\_\_\_

Dry Fired: I. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull(lbs.)I. 5.255.25 2. 5.003. 5.50Bolt Release Force(lbs.)

I. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Gun Weight: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Center of Gravity: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

• Tester and Date: \_\_\_\_\_

CJS  
I-12-82

After 2,000 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS &amp; AUTOLOADERS)

## TEST PROCEDURE SHEET

Model 700 614MSerial No. A6744869

Headspace as Received: \_\_\_\_\_

Safe - "ON" - I. 8.5"OFF" - I. 4.5

Proof: \_\_\_\_\_

2. 8.52. 5.0Headspace after Proof: M+.0043. 7.03. 6.5

Firing Pin Indent(in.)

I. .0242. .0233. .023*Scam  
lift .012  
eng. .015*

Bolt Open Force(lbs.)

Cocked: I. \_\_\_\_\_

Dry Fired: I. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull(lbs.)

I. 5.52. 5.53. 5.25

Bolt Release Force(lbs.)

I. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: \_\_\_\_\_

Gun Weight: \_\_\_\_\_

Center of Gravity: \_\_\_\_\_

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

• Tester and Date: \_\_\_\_\_

CJS  
I-12-82

After 2,500 Rounds 6-11-82

(2)

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)TEST PROCEDURE SHEETModel 700 6MMSerial No. A6744869

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.0"OFF" - 1. 5.5

Proof: \_\_\_\_\_

2. 7.02. 4.5Headspace after Proof: MT004

(7.0)

3. 7.0

(4.8)

3. 4.5Firing Pin Indent (in.)Bolt Open Force (lbs.)1. .021

Cocked: 1. \_\_\_\_\_

Dry Fired: 1. \_\_\_\_\_

2. .021

2. \_\_\_\_\_

2. \_\_\_\_\_

3. .021

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull (lbs.)Bolt Release Force (lbs.)1. 6.5

1. \_\_\_\_\_

2. 5.25

2. \_\_\_\_\_

3. 5.5

3. \_\_\_\_\_

Gun Length: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Gun Weight: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Center of Gravity: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: \_\_\_\_\_