

18

XX

.222 CALIBER MODEL 7, MODEL 700 RDL (301) 921321

RECEIVER MEASUREMENTS

MODEL 700

(2 RDL, 23 BDL RIFLES)

DWG NO.	SERIAL NO.	DWG. DIMENSIONS			ACTUAL DIMENSIONS
NO.	B-6256211	MIN.	MAX.	MEAN	
MEASUREMENT NO.					
1	1.700	1.730	1.715	1.720 ✓	
2	.015	.018	.0165	.014	
3	13° REF. L.			13°	
4	.245	.255	.250	.360	
5	2.045	2.055	2.050	2.080	
6					
7	.695	.705	.700	.840	
8	.020 R			.005 R	
9	33°			163°	
10	.055	.065	.060	.072	
11	30°			30°	
12	.281 TYP.			.281 TYP.	
13	.163	.173	.168	.162	
13a	.163	.173	.168	.162	
14	4.4075	4.4175	4.4125	4.531	
15	7/16 R. TYP.			NONE	
16	.535	.545	.540	.544	
17	.968	.978	.973	.970	
18	.180 R	.205 R	.1925 R	.190 R	
19	.072 BAGE			.072	
20	2.936	2.944	2.940	2.940	
21	.180 R	.205 R	.1925 R	.190 R	
22	.835	.845	.840	.850	
23	4.530	4.535	4.5325	4.531	
24	37°			37°	
25	.282	.288	.285	.293 ✓	
25a	.282	.288	.285	.293 ✓	
26	.055	.063	.059	.060	
27	.278 R	.280 R	.279 R	.280 R	
28	.700	.703	.7015	.700	
29	.449	.452	.4505	.451	
30	.015	.025	.020	.033 ✓	
31	20°			20°	
32	.025 R			.005 R	
33	ROUND OFF SHARP CORNERS			SHARP	
34	STRAIGHT & PARALLEL			11	
35					
36	.004	.004	±.004	±.006 ✓	