

SPORTING ARMS-AMMUNITION-TARGETS-TRAPS

ILION, NEW YORK 12357

TELEPHONE 015 894-9961

To:W.H.Coleman II
T.C.Douglas

W.Erickson J.R.Snedeker

From: F.E. Martin

Jack of gasolin the ment of preparing this parast with sween furein 100 the convenient the abrasion is a common concern but the volithity is. This is like puthing a both of lighter fluid in every box.

Also, perhaps the label should reart for bore closuring only - 10 was are no fair

At the request of W.Erickson testing to determine the affect of mistakenly applying "Rem-Clean" to trigger assemblies of Remington firearms was started.

Six sample trigger assemblies were obtained and sent to the test lab for dry cycle test. A target life of 50,000 cycles was chosen along with a test procedure. A method of continuous application of "Rem-Clean" was set up and cycling started. Testing continued to approximately 21,900 cycles when failure occured. It has been determined that this failure continuous follow down, was the result of the constant application of "Rem-Clean" to the trigger assembly. Examination of the trigger components showed excessive wear on the trigger connector and sear safety cam. Both Sear Surfaces severed are

Your comments on this subject are requested to help in developing a positive path forward for this product. Included with this letter is a sample of the subject product the Material Safety Data Sheet and brocure describing this item and its use. Please forward all comments to the writer.

Went 50,000 with we problem.

EXMIBIT C